

RICHARD L. TEMPLIN, JR.
CONSULTING ENGINEER AND FORESTER
1004 N.W. HAWTHORNE
GRANTS PASS, OREGON

December 10, 1956
FIELD NOTES OF SURVEY
OF
DEPENDENT RESURVEY AND
SUBDIVISION OF SECTION 22? 26
T. 32 S., R. 5 W., W.M.

Survey executed in November 1956 for
Sunny Valley Lumber Co.
Grants Pass, Oregon

Commencing at the center $\frac{1}{4}$ section corner of section 26, T. 32 S.,
R. 5 W., W.M. which is a car axle from which:

- A 36" D. fir bears S $69\frac{1}{2}^*$ W 162.4 ft. distant
blazed for face
- A 18" Madrone bears N 34^* W 179.5 ft. distant
blazed for face

thence

N $89^* 25'$ W on a true east-west centerline of section 26

680.1 Point for C-E-NW $\frac{1}{64}$ section corner which is an iron pin
of 1" diameter.

1360.2 Point for CW $\frac{1}{16}$ section corner which is a 1" iron pin in a
bridge fill on the east side of Quines creek from which:
A 12" Cedar bears N 63^* W 102.0 ft. distant mkd. $\frac{1}{16}$ CSBT
A 14" D. fir bears N 39^* E 97.1 ft. distant mkd. $\frac{1}{16}$ CSBT
A 20" D. fir stump bears N 19^* W 73.7 ft. distant mkd. BT

I then go to the NW $\frac{1}{16}$ section corner of section 26 which
is an angle iron from which:

- A 20" Pine bears N $51^* 30'$ E 11.1 ft. distant
Scribing visible
- A 20" Pine bears N $68^* 25'$ W 27.8 ft. distant
Blaze healed

thence

N $89^* 51'$ E on the true east-west centerline of the NW $\frac{1}{4}$ of
section 26

681.3 Point for SE NW $\frac{1}{64}$ section corner which I monument with a
 $\frac{3}{4}$ " iron pipe 24" in length driven 18" in the ground from
which:

- A 12" D. fir bears S 57^* W 10.2 ft. distant
mkd. $\frac{1}{64}$ RE 3024 BT
- A 10" D. fir bears N 87^* W 20.5 ft. distant
mkd. $\frac{1}{64}$ RE 3024 BT

MEMBER P. E. O.
MEMBER S. A. F.
MEMBER A. C. F.

RICHARD L. TEMPLIN, JR.
CONSULTING ENGINEER AND FORESTER
1004 N.W. HAWTHORNE
GRANTS PASS, OREGON

FOREST MANAGEMENT
TIMBER CRUISING
LAND SURVEYS
ROAD LOCATIONS

SURVEY OF SECTION 26, T. 32 S., R. 5 W., W.M. (Cont.)

- 1362.6 Point for CN 1/16 section corner which is a 3/4" iron pipe from which:
A 30" D. fir bears S 38* E 23.4 ft. distant
bark scribed
A 8 " Madrone stub bears N18* W 5.9 ft. distant
scribe visible

I then go to the C-E-NW 1/64 section corner previously described,

thence N 3*41' W on the true north-south centerline of the S $\frac{1}{4}$ NW $\frac{1}{4}$ of section 26,

- 1314.9 Point for SE NW 1/64 section corner previously described.

This survey was executed with a Leupold Mountain Transit, 200 ft. steel tape, and abney in good adjustment. Distances were measured on the slope and converted to the horizontal trigonometrically.

The purpose of the survey was to establish cutting lines for logging operations on the E $\frac{1}{2}$ SE $\frac{1}{4}$ NW $\frac{1}{4}$. These lines were all blazed, and merchantable trees outside the property were blazed on the side facing the property with three vertical blazes.

Bearings were based on information obtained from the Douglas County Surveyors office.

