

Oct. 21, 1957

West 1/4 Section Corner
Sec. 19, T28S, R4W, W.N. 4J

det. by Q. B. T. 389.8' O.B.T.
26" W.O. bears S2°E 389.8' O.B.T.
26" W.O. bears N15°E 155.0'

dist. found scribe O.B.T.

At corner point set 2" x 24"
1. Pipe in mound of stone.

from which

8" W.O. bears N10°E 146.5'
dist. mkd. 1/4 S 19 B.T.

6" W.O. bears N43°E 51.6'
dist. mkd. 1/4 S 19 B.T.

9" W.O. bears N32°W 50.0'
dist. mkd. 1/4 S 24 B.T.

20' x 20' x 6' high rock mound
in saddle of main ridge
bears N52°W 245.0' dist.

Witness:

C. N. Copper

R. G. Boyd



C. S. File No. 42/315

Work done for Staman Lbr. Co.

(OVER)

Note:

The most southerly B.T.
should have been at 343.0'
but I find it at 389.8'

There is a difference of 47.0'
Note also that Gov't on rechain-
ing found South $\frac{1}{2}$ mile 52.7' long.

J.A.M.

FILED
RECEIVED

OCT 30 1957

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.