



FD. 1/2" x 2" BAR - 4 ORIG. B.T.'s
BLAZED & SCRIBED NEW B.T.'s

SECTION COR. 6, 7

CLOSING COR. 1, 12, SET
5/8" ROD FROM 2 ORIG. B.T.'s
BLAZED & SCRIBED NEW B.T.'s

20" Fir - N 25° E 34.0 FT. M'KD.
T30S R4W, S-6, C.S.B.T.

30" Y" Fir - S 35° E 29.0 FT. M'KD.
T30 R4, S-7, C.S.B.T.

7" LAUREL (DEAD) - S 22° W 35 LKS
40" PINE - N 66 1/2° E 53 LKS.

20" Fir - N 58° W 25.4 FT. M'KD.
T30S, R5W, C.C.S-1, C.S.B.T.

14" Fir - S 39 1/2° W 25.2 FT. M'KD.
T30S, R5W, C.C.S-12, C.S.B.T.

1/4 COR. SEC. 1, 12 - SET
5/8" ROD FROM 10" Bl. OAK B.T.

BLAZED & SCRIBED NEW B.T.'s

30" Fir N 8° W 39.0 FT. M'KD
1/4 S-1, C.S.B.T.

20" Fir S 70° E 56.3 FT. M'KD
1/4 S-12, C.S.B.T.

N 89° 32' 30" E 2397.6

1243.2

1154.4

N 89° 43' E 2545.6 (RECORD)

E 1/4 COR. SEC. 1, 12
SET 1/2" I.P. - BLAZED &
SCRIBED 6" FIR S 25° W
9.2 FT. M'KD E 1/4 S-12, R.E.
N° 2741, C.S.B.T.

CIR 1/4 COR. (BY AGREEMENT)
SET 1/2" I.P. - BLAZED AND SCRIBED

8" CEDAR - S 70° W 10.4 FT.
8" CEDAR - S 85° E 20.7 FT.
BOTH M'KD. C 1/4 S-12 (AGR) C.S.B.T.

FD. SCRIBED LAUREL POST & ORIG. B.T.

7" Fir (NOW 20") S 43 1/4° E 8 LKS - (GOOD CONDITION)
SET 1/2" I.P., FIR STAKE ALONGSIDE.
1/4 COR. SECTIONS 11, 12

C-E 1/4 COR. (BY AGREEMENT)
SET 1/2" I.P. - BLAZED & SCRIBED

20" LAUREL - S 10° E 22.1 FT.
10" LAUREL - Y - N 35° E 29.0 FT.
BOTH M'KD. C-E 1/4 S-12 (AGR)
R.E. 2741 - C.S.B.T.

SEC. COR. 7, 12, 13, 18
SET 5/8" ROD FROM 2 ORIG. B.T.'s
BLAZED & SCRIBED NEW B.T.'s

30" Fir - N 34° E 27.5 FT. M'KD.
T30S, R4W, S-7, C.S.B.T.

10" PINE - N 22° W 18.1 FT. M'KD
T30, R5, S-12, C.S.B.T.

20" PINE - S 15° E 33.7 FT. M'KD.
T30, R4, S-18, C.S.B.T.

SET 5/8" ROD FOR SOUTH
1/4 COR. SEC. 12 (BY AGREEMENT)
BLAZED & SCRIBED

12" LAUREL N 5° E 18.5 FT.
20" LAUREL N 85° E 35.0 FT.
BOTH M'KD. So. 1/4 S-12 (AGR)
C.S.B.T.

FD. LAUREL TREE - BLAZE CHOPPED
OUT & ROTTED, NO MARKS LEG-
IBLE. PROPERTY OWNERS AGREED
TO ITS USE TO FIX 3/4 COR. OF
SECTION 12.

Not common - see letter
P.L.M.A. 8/1/51

1/4 COR. SEC. 12, 7 - SET 5/8" ROD BY
PROPORTIONAL MEAS. - BLAZED &
SCRIBED 20" FIR - N 40° E 23.2 FT. M'KD
1/4 S-7, T30, R4, R.E. 2741 - C.S.B.T.

14" FIR - N 29° W 23.0 FT. M'KD
1/4 S-12, T30, R5, R.E. 2741 - C.S.B.T.

NOTE -
BEARINGS SHOWN ARE TRUE, BASED
ON SOLAR OBSERVATION MADE DURING COURSE
OF THIS SURVEY

COUNTY SURVEYOR'S OFFICE
DOUGLAS COUNTY, OREGON

SURVEY TO ESTABLISH PROP-
ERTY CORNERS IN SECTION 12,
T30S., R5W., W.M.

BEN. B. IRVING COUNTY SURVEYOR
SURVEYED JULY, AUGUST, 1951 BY
A.R. EVANS DEPUTY

SCALE 1" = 400'



CS FILE FOLDER

CONTAINS

MORE

INFORMATION