

INDEX DIAGRAM

Township 28 SOUTH, Range 9 WEST,

6	5	4	3	2	1
7	8	9	10	11	12
13	17	16	15	14	13
3			8 9	6	5
19	20	21	22	6 23	24
			8		4 5 3
20	29	28	27	26	25
		9	7 7		
2 31	32	33	34	35	36
	1 1				

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CHAINS

Remonumentation, Original Corner Points, T. 28 S., R. 9 W.

The cor. of secs. 13, 18, 19 and 24, on the W. bdy. of the Tp., determined at record bearing and distance from the original bearing trees:

A cedar, 50 ins. diam., bears N. 55° E., 42 lks. dist., with scribe marks T28S R9W S visible on partially healed blaze.

A maple, 30 ins. diam., bears S. 77° E., 38 lks. dist., with no marks visible on partially healed blaze. (Record bearing, S. 83° E.)

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 28 S
R 10 W | R 9 W
S 13 | S 18
S 24 | S 19
1962

from which new bearing trees and a bearing object:

A maple, 25 ins. diam., bears N. 46° E., 70 lks. dist., mkd. T28S R9W S18 BT.

A myrtle, 35 ins. diam., bears S. 42° E., 24 lks. dist., mkd. T28S R9W S19 BT.

A fir, 24 ins. diam., bears West, 55 lks. dist., mkd. T28S R10W S24 BT.

A sandstone outcrop, 15 ft. high, bears N. 45° W., 33 lks. dist., mkd. B X O.

Corner Remonumentation on the East Boundary of
T. 28 S., R. 9 W.
(Remonumenting a corner established
by Dennis Hathorn in 1855)

The cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., monumented with an iron pipe, 1½ ins. diam., firmly set, protruding 14 ins. above the ground, with brass cap mkd. Doug. County Surveyors Office.

Surveyors
T 28 S
Doug. Co. R 9 W | R 8 W Office
Coos Co. S
24 | 19
25 | 30
1957

from which the three remaining original bearing trees:

A fir, 48 ins. diam., bears N. 78° E., 31 lks. dist., with a healed blaze.

A rotted hemlock stump, bears S. 50° E., 5 lks. dist., with no marks remaining.

Add to Ren #83

CHAINS

Remonumentation, Original Corner Points, T. 28 S., R. 9 W.

A rotted fir stump, bears S. 65° W., 5 lks. dist., with no marks remaining.

and the County Surveyor's bearing trees:

A hemlock, 12 ins. diam., bears N. 44° E., 60 lks. dist., mkd. T28S R8W S19 BT DCS.

A hemlock, 12 ins. diam., bears S. 80 $\frac{1}{2}$ ° E., 25 $\frac{1}{2}$ lks. dist., mkd. T28S R8W S30 BT DCS.

A down hemlock, 8 ins. diam., bears S. 58 $\frac{3}{4}$ ° W., 15 lks. dist., mkd. T28S R9W S25 BT DCS.

A down hemlock, 36 ins. diam., bears N. 85 $\frac{1}{2}$ ° W., 31 lks. dist., mkd. T28S R9W S24 BT DCS.

and two new bearing trees:

A hemlock, 10 ins. diam., bears S. 12 $\frac{1}{2}$ ° W., 30 $\frac{1}{2}$ lks. dist., mkd. T28S R9W S25 BT.

A hemlock, 13 ins. diam., bears N. 32° W., 138 lks. dist., mkd. T28S R9W S24 BT.

Add the mks. BLM 1962 to the County Surveyor's brass cap

Corner Remonumentation on the Subdivisional Lines of T. 28 S., R. 9 W.

(Remonumenting corners established by W. S. Chapman, in 1875)

The cor. of secs. 23, 24, 25 and 26, monumented with an iron pipe, 1 $\frac{1}{2}$ ins. diam., firmly set, protruding 10 ins. above the ground, with a $\frac{3}{4}$ in. steel rod inside, and mkd. with a seal, number 401, from which the three remaining original bearing trees:

A hemlock stub, which has slid down the hill, 20 ins. diam., bears N. 15° E., 4 lks. dist., no marks remaining on opened blaze. (Record, N. 16° E., 50 lks. dist.)

A fir stump, 54 ins. diam., bears S. 46° E., 24 lks. dist., no marks remaining on opened blaze.

An uprooted and moved sawed fir stump, bears N. 82° W., 13 lks. dist., with scribe marks 28 S visible on opened blaze. (Record, N. 47° W., 23 lks. dist.)

and a tree not of record:

A hemlock, 9 ins. diam., bears S. 31° E., 255 lks. dist., mkd. S25 BT.

At the corner point

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.

T 28 S R 9 W
S 23 | S 24
S 26 | S 25
1962

from which new bearing trees: