

RENEW

27/26
34/35

T 245 R 7W

FOUND - ORIG 36" NEW 48" CLEAR
 585' W 1016' CENTER ROTTED
 NO SCRIBING FD. SHOWS OLD BLADE
 NO AXE MARKS. I FIND NEW 36" PARTLY
 ROTTED TIE, AND CHECKS RECORD
 DISTANCE FOR ORIG. N 1/2 BIT
 NO SCRIBING FD. I FIND STUMP HOLE
 THAT CHECKS BEARING & DISTANCE
 ORIG. T W BIT. I FIND TRACE OF ORIG.
 T W BIT FD. I FIND 10" X 1 1/2" X 6"
 LAYSTONE OUT ON GROUND BUT AT
 CORNER MARKED WITH 2" T ON TOP
 OF C S ON FACE.

SET BRASS CAP AT CORNER MKD.
 COUNTY SURVEYORS OFFICE 1958

530536 T 245 R 7W

530535 RESET FOR STONE ALONGSIDE
 BRASS CAP

NEW BIT

12" P. TIP BEARS N 15° W 152'
 SCRIBED 527 T 245 R 7W C S BIT

14" P. TIP BEARS N 49° E 40.6'
 SCRIBED 526 T 245 R 7W C S BIT

14" P. TIP BEARS S 59° W 388'
 SCRIBED 534 T 245 R 7W C S BIT

8" P. TIP BEARS S 74° E 411'
 SCRIBED 532 T 245 R 7W C S BIT

DIETZEN NO. 385-B

*
 FILED
 RECEIVED

AUG 18 1959

AUG 18-59

J. B.

M. S.

C. S.

COUNTY SURVEYOR
 DOUGLAS COUNTY, ORE.

C. S. File No. 49/41-23