

16115

RENEW 21 22 T 275 R 5 W

FOUND - ORIG. 20" NAIL W. OAK SHOWS
GOOD SCAP CENTER 20" TO D. I.C. 10"
279.8' ORIG. 4" NAIL 22" OAK STUMP CENTER
ROTTED SHOWS GOOD REVERSE SCRIBING
"S" & "N" N 88 1/2° E 62.7' TO FIND NO
EVIDENCE OF ORIG. OR BT.

NOTE - CORNER IS IN FIELD. T. SET
W. T. COR. 8' EAST OF SEC. COR.

SET BRASS CAP IN N. S. FENCE LINE
1/2 8' EAST OF SEC. COR. MARK
W. T. COR. 8' WEST TO SEC. COR.

SIG/SIS COUNTY SURVEYORS OFFICE 1959
T 275 R 5 W
521 522

NEW BT'S

9" W. OAK BEARS S 85 1/2° E 317'
W. C. 522 T 275 R 5 W C 5 BT

18" W. OAK BEARS S 3° W 205'
SCRIBED S 21 W. C. T 275 R 6 W C 5 BT

NO OTHER BT'S VIEW

VAR 20 1/2°

JULY 16 - 59
J. B.
M. G.
C. P.

*

FILED
RECEIVED

JUL 21 1959

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

✓ ✓ C. S. File No. 49/62-3

DIETZEN NO. 386-6

T 27 S R 5 W

FD. W. OAK (36" DIAM.)

16	15
21	22

S $6\frac{1}{2}^{\circ}$ W 279.8 FT. HAD BEEN
OPENED PREVIOUSLY & ROTTED OUT
INSIDE.

FD. OLD OAK STUMP (16" DIAM.)

N $88\frac{1}{4}^{\circ}$ E 623.7 FT SHOWING
REVERSE SCRIBING INSIDE (HOLLOW)

FD. OAK STUMP - DOWN -

S $54\frac{1}{4}^{\circ}$ E APPROX. AT DIST. CALLED
FOR - DID NOT CHOP OPEN -

COR. POSITION FALLS IN
FIELD APPROX. 28 FT. NORTH
& 9 FT. WEST OF FENCE COR.

DID NOT SET CORNER.

July 7, 1959