

T 30 S R 5 W

COR SECS

4/3
9/10

FIND WOODEN STAKE AT
CORNER AND ROTTEN SNAG
OF AN OAK (APPROX. 10" DIAM.)
S 22 1/2° W 27 FT REVERSE
SCRIBING ON INSIDE OF SNAG,
"S 9 T 30 S R 5 W BT" VISIBLE.
NO SIGN OF CORNER TREE
OR ANY OF THE OTHER B.T.S.
CAN BE FOUND.

AT COR. SET IRON PIPE WITH
BRASS CAP MARKED "COUNTY
SURVEYOR'S OFFICE 1959 T 30 S
R 5 W S 4 | S 3
S 9 | S 10

BLAZE & SCRIBE FOLLOWING
NEW B.T.S.:

- 18" DOUGLAS FIR S 5° W 14 5/8 FT.
MKD. "T 30 S R 5 W S 9 CS BT."
- 15" DOUGLAS FIR S 58° E 25 8/8 FT.
MKD. "T 30 S R 5 W S 10 CS BT"
- 9" DOUGLAS FIR N 62 1/2° E 8 0 FT.
MKD. "T 30 S R 5 W S 3 CS BT"
- 15" DOUGLAS FIR N 25° W 43 8 FT.
MKD. "T 30 S R 5 W S 4 CS BT"

MARCH 12, 1959

O. V.

J. W. B.

*

✓ U.S. FILE NO.

49/107-4