

RENEW $\frac{1}{4}$ COR. 11/12 T22S R12W

FD 1 1/2" IP AT COR. & BOTH ORIG.
BTS. CORNER 15" NOKY 32" HEMLOCK STUMP
EAST 47" SHOWS GOOD SCRIBING 1/4" S
ORIG 2 1/4" NOKY 36" HEMLOCK STUMP
S BRW 3 1/2" SHOWS GOOD SCAR, I DO
NOT OPEN.

NOTE - BEARINGS CHECK RECORD
BUT DISTANCES MEASURED ON GROUND

SET BRASS CAP ALONGSIDE BOLL PILE
MARKED COUNTY SURVEYORS OFFICE
1959. $\frac{1}{4}$ 511 15 2 T22S R12W

NOTE - COR. IN BOTTOM OF NORTH
SOUTH DRAW

NEW BT
12" HEMLOCK BEARS BR 5 1/2" E 3 1/2"
SCRIBED 1/4" S W BT

NO TREES NEAR TO WEST

JUNE 3, 1959

DIETZEN NO. 388-6

FILED
RECEIVED

JUN 4 1959

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

*

C. S. File No. 19/153

RENEW $\frac{1}{4}$ COR 10/11 T22S R12W
FOUND - DRIG 60" NOW 60" FIR STUMP
S 85° W 16.5 PREVIOUSLY OPENED SHOWS
GOOD SCRIBING "4.5". I FIND NO TRACE
OF DRIG. NE BT

SET BRASS CAP AT CORNER MINN
COUNTY SURVEYORS OFFICE 1959
 $\frac{1}{4}$ S10/S11 T22S R12W CS BT

NEW BTS.
40" CEDAR STUMP S 2° E 7'-
SCRIBED $\frac{1}{4}$ S CS BT.
18" HEMLOCK N 80° W 15'-
SCRIBED $\frac{1}{4}$ S 10 CS BT.

VAR 20 $\frac{1}{2}$ °

JUNE 3-59

J.B.

J.B.

*

✓✓