

MARVIN C. RAMSEY
REGISTERED PROFESSIONAL LAND SURVEYOR
FOR OREGON

PHONES: GR 6-5647 GRANTS PASS
1228 CAVE JUNCTION

July 17, 1959

724 N. E. MADRONE STREET
GRANTS PASS, OREGON

Fred M. Darby
County Surveyor
Roseberg, Oregon

Dear Mr. Darby:

At the request of J. H. Baxter & Co., I started at the sec. cor. of secs. 15, 16, 21 and 22, T. 29 S., R. 7 W. W. M. I find the sec. cor. in order as described by Hans W. Thielson in 1957. I ran South a mile and failed to find the sec. cor. to secs. 21, 22, 27 and 28.

At the $\frac{1}{4}$ sec. cor. bet. secs. 22 and 27, T. 29 S., R. 7 W. W.M. I determine the cor. point from the only extant original bearing tree, a Douglas fir snag 20 ins. diam., bears S. 45° W., 28 lks. dist., mkd. $\frac{1}{4}$ S BT. Set an iron pipe 3 ft. long $1\frac{1}{2}$ ins. diam., 28 ins. in the ground, mkd. RS404 and take new bearing trees.

A white fir 8 ins. diam., bears S. $68\frac{1}{2}^{\circ}$ W., 29 lks. dist., mkd. $\frac{1}{4}$ S27 RS404 BT.

A Douglas fir 18 ins. diam., bears N. 57° W., 30 lks. dist., mkd. $\frac{1}{4}$ S22 RS404 BT.

Thence I ran West $\frac{1}{2}$ mile and failed to find the sec. cor. to secs. 21, 22, 27 and 28 after careful search. ✓

I am so sorry that I couldn't continue the survey and set the sec. cor. of secs. 21, 22, 27 and 28 on double proportion, but when my pay stops I have to quit, so all I could do for you is to rehabilitate the $\frac{1}{4}$ sec. cor. bet. secs. 22 and 27.

Sincerely yours,

Marvin C. Ramsey
Marvin C. Ramsey

P.S. The $\frac{1}{4}$ sec. cor. 22 and 27 was rehabilitated on July 7, 1959.

FILED
RECEIVED

JUL 20 1959

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

C. S. File No. 51/32