

G. ROBERT LECKLIDER

ENGINEER

P. O. BOX 368

PHONE ORCHARD 3-3302
ROSEBURG, OREGON

July, 1959

CLOSING CORNER OF SECTIONS 9 & 10, T 27 S, R 2 W:

FOUND: $1\frac{1}{2}$ " Galv iron pipe for corner from which:
 30" Fir bears S 78* E-31.0 feet (Orig. B.T.; now a stump; scribe vis.)
 30" Fir bears S 63* W-79.0 feet (orig B.T.; now a stump; scribe vis.)
 24" Pine bears N 13* E-12.9 feet (8 ft. stub; badly decayed; scribe vis.)
 12" Fir bears S 52* W-40.2 feet (now a stump with remainder of tree near;
 scribe vis.; mkd. CS; no record of this B.T.)
 16" Fir bears N 79* W-70.6 feet (now dead; chopped open; scribe vis.)
 1957 GLO Brass Cap bears N 1* 57' E-11.0 feet (Also new B.T.'s. referring
 to this Brass Cap in GLO records.)

SECTION CORNER OF SECTIONS 3 & 4, T 27 S, R 2 W:

FOUND: A shallow hole in the ground 70.0 feet West of the Closing Corner
 of Sections 9 & 10 described above from which:
 30" Fir bears N 51* W-93.0 feet (Orig. B.T.; badly decayed; reverse
 scribe plainly visible on thin pitchy shell; now a stump)
 1957 GLO Brass Cap bears N 48* 34' W-14.0 feet (Also new B.T.'s. referring
 to this Brass Cap in GLO records.)

NOTE: The closing corner of sections 9 and 10 was renewed as a common corner in
 1929 by Ben Irving. In 1935 it was renewed again by Eppstien as a common
 corner.

FILED
RECEIVED

JUL 30 1959

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.C.S. File 51734

∞

Map File M 15730