

ARTHUR BOYER
ROSEBURG, OREGON

RENEWAL S. 1/4 Cor Sec 30, T. 26 S; R. 8 W; W.M. (N.1/4 cor 31)
Found lower scribed blaze on stump of wit. tree in sec. 30 and
rotted stump of tree in sec. 31, both orig. trees and from them
located corner driving a 1" by 30" steel shaft here, marking two
wit. trees, an 18" Fir, N.44°W. 25.0' and an 8" Fir S.31°W. 16.3'
scribed 1/4 S.30 and 1/4 S/31 resp., 1581 B.T., msmts to cen. trees.
Sept 30, 1959
Wits. Harvey Eppstein, Donald Wood
A.B.

RENEWAL SEC. COR Secs.30 & 31, 26 S;R.8 W; Secs 25 & 36, R.9 W.
Ran a line W., on a 20° decl; from S.1/4 cor Sec. 30, a dist of 2640'
then from the found 1/4 sec. cor. between Secs. 31, 26/8 W. and 36,
26/9 W; ran 2640 ft. N., on 20° decl; to a point, then searched in 36
for the sec. cor. for S.30, 31, 25 and 36 and found a fir snag on
the bark of which was distinct signs of the blazes for the wit. tree
but the inside of the bark marking was rotten wood where the scribe
would have been, also found the snag of the wit. tree in sec. 31
which showed signs of having been axed out for the markings; Fire
destroyed most of the trees here. When the corner was set from these
two trees, the bearings and distances matching, the corner fell
S. 45°E. 18 ft. from a point measured N. 2640 ft. from the 1/4 cor.
bet 31 and 36, using a 20° decl., and 2.9 ft. N. of a point which is
W. 2659' from the S. 1/4 cor of 30, using 20° decl; drove a 4" by 4"
fir post for the corner and blazed and scribed an 18" fir N.77°E. 4.0'
mkd. S.30 T.26S;R.8 W; 1581 B.T. a 12" Fir S.30°E. 20' mkd. S.31
T 26S R8W 1581 B T. a 24" Fir S 37°W. 26.6' mkd. S.36 T.26 S R.9 W
1581 B.T. a 24" Fir N 64°W. 7.9' Mkd. S 25 T 26 S R 9 W 1581 B.T.
all measurements to the center of trees.

Oct. 1, 1959
wits. Harvey Eppstein Donald Wood
A.B.

This cor is on the E slope
of a N.& S. ridge, 50' S. of
top of ridge, abt. 100' W of
small ck. a vert. rock bluff
is abt. 100' to 150' E; runng.
E.& W. with sec. line.

ESTABLISHMENT 1/16th cor. S. side SW 1/4 sec. 30
From a line run bet. S 1/4 cor. Sec. 30 and SW cor 30, 26/8, set
the 1/16th cor on S. side SW 1/4 30 by proportional measurement,
1325.6' W. of S 1/4 cor sec. 30 and on line bet. S 1/4 and SW cor
of sec. Drove a 1" by 16" steel roller for the corner and a squared
wooden stake from which a wit tree, a 24" cedar was blazed and scribed.
marked 1/16 S.30 T 31 S.55°E. a distance of 35.0 ft. to the center
of tree. 1581 B.T. This cor is in the channel of a small stream
running E & W; ten ft. N. of the cen. of stream, the walls of which
are very steep, especially to the N. which is abt. 40°
brush on hillside is thick. sec. line, S.sd. 30, crosses ck. abt.
40' W. of 1/16th corner.

Oct. 5th 1959
A.B.
witnss. Harvey Eppstein Glenn Wood

no more cornrs set this year, threatening storms prevent further operatns

Arthur Boyer