

February 6, 1961

Restoration of 1/4 Corners - Section 12, 13, Township 27 South
Range 3 West, Willamette Meridian

This 1/4 corner was restored by the use of distance calls on two Creek from the G.L.O. notes which read as follows:

East on random line between Sections 12 and 13,
38.70 stream, 3 lks. wide, course N.W.
39.90 stream, 3 lks. wide, course N.W.
40.00 set tem. 1/4 section corner
79.30 Intersect twp. line thence S89° 47' W on true line
39.65 Set 1/4 sec. corner

In measuring from the section corner of 11,12,13,14 to the section corner of 7,18, Township 27 South, Range 2 West and Sections 12,13, Township 27 South, Range 3 West, this line was found to be N 89° 26' E a distance of 5160.90 feet. The bearing of N 89° 26' E was used for control North and South and the calls on the above creeks was used for control east and west; the distance between the creeks was found to be 84.3 feet as compared to the original distance of 79.2 feet given in the G.L.O. notes. The corner was set by proportionment of the old distance to the distances we found in the field with the following new distances to the creeks, 17.6 feet instead of 16.5 feet to the creek East of the corner and 66.7 feet instead of 62.7 feet to the creek west of the corner.



FILED
RECEIVED

FEB 7 1961

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

C. S. File No. 51/174