

SURVEY NO. _____ IN SEC. _____ T. _____ R. _____ W.W.M.
DOUGLAS CO. OREGON

MADE FOR Coos Head Timber Co. DATE Dec 1954 - Feb. 1961

MADE BY C. A. Stephens REGISTERED PROFESSIONAL ENG.

ORE. NO. 238 DATE OF REGISTRATION May 7, 1948

This was a compass and chain survey for the purpose of road location and timber removal from the lands of the Coos Bay Timber Co. The survey commenced with the running of a road traverse in Section 6, Twp. 31 S., R. 9 W., and to a point 700 feet westerly of the 1/4 Corner between Sections 8 and 9, Twp. 31 S., R. 9 W., W.M. This was done in January, 1958.

*1/4 corner
marked*

South between Sections 8 and 9, T. 31 S., R. 9 W., from the 1/4 Corner. Set 1/2" Gal. iron pipe and post for 1/4 Corner from which:

A fir 16" in Dia. brs. S 35° W.

A fir 26" in Dia. brs. S 15° E. 22.4 Feet ✓✓✓

Thence: South on trial line between Sections 8 and 9, T. 31 S., R. 9 W.

6+23.6 Cross logging road bearing SE - NW

26+12.3 Intersect Section line between Sections 9 and 16 22.2 Feet west of the Section Corner common to Sections 8, 9, 16 and 17. Find Cedar marked for the corner down. Set iron pipe post at roots of down Cedar for the corner from which:

A Fir 16" in Dia. brs. N 42° E 6.6 Ft. orig. BT
(Scribing visible)

A fir 24" in Dia. brs. S 40° E 23.2 Ft. orig. BT

a fir 10" in Dia. brs. S 45° W 22.4 Ft. orig. BT ✓✓

January 14, 1958

Thence: N 00° 03' W on true line between Sections 8 and 9, 2,612.3 Feet to 1/4 Corner between Sections 8 and 9, T. 31 S., R. 9 W.,

FILED
RECEIVED

FEB 27 1961

COUNTY SURVEYOR
DOUGLAS COUNTY, OREGON

Continuing from Section Corner to Sections 8, 9, 16 and 17, T. 31 S., R. 9 W.
South on trial line between Sections 16 and 17 at 5,331.0 feet. Intersect Section line between Sections 16 and 21 60.8 feet east of the corner to Sections 16, 17, 20 and 21. Find two BTs remaining. Corner falls under 60" Dia. down Fir log. Set post on East side of log from which:

A Fir 38" in Dia. brs. S 45° W 66.0 feet.
(face not opened)

A Fir 30" in Dia. brs. S 38° E 85.6 feet (Scribing visible) ✓ ✓ ✓

The BTs in the NW and NE quadrant gone.

Thence:

N 00° 31' E on true line between Sections 16 and 17.

At: 1332.75 feet set S 1/16 corner between Sections 16 and 17 on true line. Set post for the corner from which:

A Fir 16" in Dia. brs. S 51½° W. 8.1 feet.
Tree scribed and BT metal tag on face.

At: 2,665.00 feet. Reestablished the 1/4 Sec. Corner (No trace of original found. BTs were Chinquapin. Set squared post and pipe for Corner from which:

A Fir 36" in Dia. brs. N 76° E 18.3 feet.

A Fir 12" in dia. brs. N 05° E 27.3 feet. ✓ ✓ ✓

December 17, 1959

5,331.0 feet to corner of Sections 8, 9, 16 and 17.

West between Sections 8 and 17, T. 31 S., R. 9 W., W.M.
2,617.6 Intersect 38.8 feet South of the 1/4 Corner.

From BTs found set post and 3/4" iron pipe for 1/4 corner from which:

A Fir 12" in Dia. brs. N 51° E - 9.2 feet
(Scribing visible)

A Cedar 12" in Dia. brs. S 45° W 27.1 feet
(down)

New BT

A Fir 24" in Dia. brs. S 40° E - 15.0 feet

FILED
RECEIVED

FEB 27 1960

COUNTY SURVEYOR
DOUGLAS COUNTY, IOWA

- 2 -

C.S. FILE 51 / 178 b

Map 1116 M20-16

Thence:

N 89° 09' E on true line between Section 8 and 17 from 1/4 Sec. Corner. A distance of 2,617.6 feet to Section Corner to Sections 8, 9, 16 and 17, T. 31 S., R. 9 W.W.M.

I now continue the survey from the Southwest corner of Section 17, the corner common to Sections 17, 18, 19 and 20, T. 31 S., R. 9 W.W.M. Find BTs in good condition and set 1/2" iron pipe and post for the corner from which:

- A Fir 38" in Dia. brs. N 70° E 23.3 feet
- A Fir 18" in Dia. brs. S 38° E 37.7 feet
- A Fir 20" in Dia. brs. S 30° W 36.6 feet
- A Port Orford Cedar 24" in Dia. brs. N 59½° W. 37.0
(Scribing visible)

All original BTs - None opened - (Scar of face visible).

March 18, 1959

West between Sections 18 and 19 from Section Corner common to Sections 17, 18, 19 and 20, T. 31 S., R. 9 W.

2,609.6 - Intersect the 1/4 Section corner (No error of closure). Find two BTs - No Rock - BT is recorded in the SW quadrant actually in SE quadrant. Set pipe and White Cedar post for the Corner from which:

- A Fir 26" in Dia. brs. S 20° E 58.1 feet
(recorded as being in SW quadrant)
- A Fir 24" in Dia. brs. N 28° E 28.4 feet (face opened for verification - found scribing)

Thence:

N 89° 56' E on true line between Section 18 and 19, T. 31 S., R. 9 W. 2,609.6 feet to Section Corner to 17, 18, 19 and 20.

PARTIAL SUB-DIVISION OF SECTION 17,
TOWNSHIP 31 S., R. 9 W., W.M.

East between Sections 17 and 20, T. 31 S., R. 9 W.

1+38.1 Cross fire road top of ridge bearing N-S then descend following old blazes to

25+81.9 Fall 10.1 feet South of the 1/4 Corner. Post gone but find both bearing trees in good condition. Set new post and 3/4"

FILED
RECEIVED

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

Gal. iron pipe for the 1/4 Corner from which:

A Fir 26" in Dia. brs. S $06\frac{1}{2}^{\circ}$ E 28.4 Feet
(B.T. tag on face)

A Fir 28" in Dia. brs. N 56° W 40.8 Feet
Both BTs original and in good state of preservation. ✓

Thence:

S $89^{\circ} 36'$ W on true line between Sections 17 and 20, T. 31 S.,
R. 9 W.

2,581.9 feet to Section corner to Sections 17, 18, 19 and 20.

East between 17 and 20, T. 31 S., R. 9 W. from 1/4

Section Corner.

26+03.5 Intersect Section Corner common to Sections 16, 17, 20 and 21.

Find two BTs remaining. Corner falls under 60" diameter down

Douglas Fir log. Set post on East side of log from which:

A Fir 38" in Dia. brs. S 45° W 66.0 feet
"Face not opened"

A Fir 30" in Dia. brs. S 38° E 85.6 feet (Scribing
visible)

The BTs in the NW and N.E. quadrants are destroyed.

Thence:

S $89^{\circ} 56' 40''$ W on true line between Sections 17 and 20.

1302.7 Set the E 1/16 Corner between 17 and 20, T 31 S., R 9 W.

Set post and 3/4" iron pipe for the corner from which:

A Fir 12" in Dia. brs. S 77° E 14.6 feet

A Fir 16" in Dia. brs. S 69° W 11.2 feet ✓

West through the center of Section 17 from 1/4 Corner between
Sections 16 and 17, T. 31 South, Range 9 W. (on a trial line)
descend to

6+58.4 Cross Gold Mountain Creek and ascend steep.

21+45.7 Cross branch of Gold Mountain Creek. Flows NE

23+68.6 Cross same creek

28+59.4 Cross same creek

39+38 Cross same creek

FILED 51+80.4 Intersect the 1/4 Corner between Sections 17 and 18 T 31 S.,
RECEIVED R. 9 W. 58.22 feet South of the 1/4 Corner.

FEB 20 1916

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

Set iron pipe on the South Side of a 36" Fir which was originally marked for the 1/4 Section Corner. Face on E and W side of tree from which:

A Fir 22" in Dia. brs. S 54° E 22.3 Feet

A Fir 18" in Dia. brs. S 12½° W 28.0 feet

(original BTs)

Bearing of true E-W 1/4 line of Section 17 is S 89° 31' W a distance of 5,180.4 feet.

December 17, 1958

The survey now continues from the 1/4 Section Corner between Sections 17 and 20, T. 31 S., R. 9 W., W.M. previously described in this survey.

North through the center of Section 17, T. 31 S., R. 9 W., W.M. There was no error of closure.

Therefore:

N 00° 23' E on true line through the center Section 17.

At 26+24.3 intersect E-W trial line.

26+53.6 Intersect E-W true line through center Section 17.

Set 3/4" iron pipe and post for the center of Section 17 from which:

A Fir 36" in Dia. brs. S 54° E 6.4 feet

A Fir 22" in Dia. brs. N 65° W 35.8 feet

Both BTs scribed and BT tag ^{of} face.

52+72.4 The North 1/4 Section Corner of Section 17 previously described in this survey.

At the mid-point or 1326.8 feet South of the CS¼ Corner I set on true line the C-C S 1/16 Corner. Set 3/4" Gal. iron pipe and post for the corner from which:

A Fir 44" in Dia. brs. S. 14° E 13.1 feet
Scribed with BT tag on face.

FILED
RECORDED

FEB 1959

- 5 -

COUNTY SURVEYOR
CLATSOP COUNTY

C.I. File 51/178E

Map File M20+16

EAST ON TRIAL LINE THROUGH THE CENTER OF THE SE $\frac{1}{4}$
OF SECTION 17, TWP. 31 S., R. 9 W., W.M.

April 16, 1960

26+06.3 Intersect the Section line between Sections 16 and 17,
14.5 feet south of the S 1/16 corner, previously described
in this survey.

Thence:

S 89 $^{\circ}$ 54' W on true line through the center of the SE $\frac{1}{4}$ of
Section 17, T. 31 S., R. 9 W. a distance of 2606.3 feet.

Continue the survey from the E 1/16 corner between
Sections 17 and 20, T. 31 South, Range 9 W. which has
previously been described.

North on trial line through center of the SE $\frac{1}{4}$ of
Section 17, T. 31 S., R. 9 W.

At:

13+21.6 Intersect the trial line E-W through the center of the
SE $\frac{1}{4}$ of Section 17.

13+28.9 on true E-W line through the center of the SE $\frac{1}{4}$.

26+62.6 Intersect true E-W 1/4 line 9.6 feet E of the C-C-E1/16
corner. This corner marked with a fir post and 3/4" Gal.
iron pipe from which:

A Fir stump 36" in Dia. brs. S 40 $^{\circ}$ W 18.9 feet
(Stump scribed and BT tag nailed to face.)

Thence:

S 00 $^{\circ}$ 27' W on true line through the center of the SE $\frac{1}{4}$.
1,328.9 feet and at the intersection of true N-S E-W 1/16
lines set the center of the SE $\frac{1}{4}$ of Sec. 17, T. 31 S., R. 9 W.

Set 3/4" iron pipe and fir post for the corner from
which:

A Fir 20" in Dia. brs. N 12 $^{\circ}$ W 10.8 feet
2,662.6 feet to the E 1/16 corner between 17 and 20, T 31 S. ✓
R 9 W.

FILED
RECEIVED

COUNTY SURVEYOR
DOUGLAS COUNTY, NEB

C.D. File 51 / 178 F

Map File M20 + 16

The E-W line through center of SE $\frac{1}{4}$ of Section 17
from the center of the SE $\frac{1}{4}$ is:

N 89 $^{\circ}$ 54' E 1303.0 feet to East Boundary Section 17
S 89 $^{\circ}$ 54' W 1303.0 feet to C-C S 1/16 Corner.

From the center of Section 17 we have:

S 89 $^{\circ}$ 31' E 1303.3 feet to C-C E 1/16 Corner
S 89 $^{\circ}$ 31' E 2606.7 feet to 1/4 Corner between 16 and 17
N 89 $^{\circ}$ 31' W 2573.7 feet to the 1/4 Corner between
17 and 18.

From the CS 1/4 (center Section 17), T. 31 S., R 9 W.,
we have:

N 00 $^{\circ}$ 23' E 2618.8 to the 1/4 Corner between 8 and 17.
S 00 $^{\circ}$ 23' W 1326.8 to the C-C S 1/16 corner.
S 00 $^{\circ}$ 23' W 2653.6 to the 1/4 Corner between 17 and 20,
T. 31 S., R 9 W.

The survey continued from Section Corner to Sections
8, 9, 16 and 17, T. 31 S., R. 9 W., W.M.

January 14, 1958

East on trial line between Sections 9 and 16, T. 31 S.
R. 9 W.

11+85.8 Cross stream flows S. W.

15+70.0 Cross Road Location

18+06.9 Top of ridge and cross trail bearing N-S

24+81.5 Intersect 1/4 Corner. 68.75 feet South of the corner. Post
gone 2 BTs remain and in position as called for in the U. S.
Government notes. Set post and 3/4" Gal. Iron pipe for the
1/4 Corner from which:

A dead Fir stub 4" in Dia. brs. S 30 $^{\circ}$ E 16.5 feet.
Face opened - scribing visible.

A Hemlock 8" in Dia. brs. N 30 $^{\circ}$ W 12.5 feet
(Face not opened) ✓ ✓

Thence:

S 88 $^{\circ}$ 16' W on true line between Sections 9 and 16 from the
above 1/4 Section Corner.

FILED
RECEIVED

FEB 23 1958

- 7 -

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

C.S. File 51/1780

Map File M20716

East on trial line between Sections 9 and 16 from
the 1/4 Section Corner.

12+39.4 Cross stream flows South.

15+35.0 Proposed logging road location.

22+70.0 Cross stream flows SW

26+09.7 Intersect East boundary of Section 9 50.1 feet North of the
Corner to Sections 9, 10, 15 and 16, T. 31 S., R. 9 W. Find
two of the original BTs. Set 3/4" iron pipe and post for the
Section Corner from which:

A Fir 32" in Dia. brs. S 39°E 52.8 feet

A Fir 18" in Dia. brs. S 40°W 30.4 feet
New BT

A Fir 40" in Dia. brs. S 71°W 25.8 feet
(Scribed and BT tag on face)

Thence:

S 89°32' W on true line between Sections 9 and 16.
2609.7 feet to 1/4 Corner.

South on trial line between Sections 9 and 10, T. 31 S.
R. 9 West from the 1/4 Corner.

January 23, 1959

Find stone marked 1/4 on face for 1/4 Corner and new
fir post. Set 3/4" iron pipe along side of post from which:

A White Fir 8" in Dia. brs. S 39°W 28.0 feet
(Scribing on face visible)

A Fir 26" in Dia. brs. N 54° E 13.2 feet

Thence:

N 01°05' E on true line between Sections 9 and 10 from
Section Corner common to Sections 9, 10, 15 and 16, T. 31 S.,
R. 9 W. (See East between Sections 9 and 16 for description
of corner.)

At: 2,602.6 feet the 1/4 Corner between Sections 9 and 10,
T. 31 S., R. 9 W.

At: 3,930.1 feet - Find post marked 1/16 and metal tag
marked W. Owen. Tree not scribed. Discontinued line
at this point. The timber had been cut to their line
by the Robert Dollar Company.

FILED
RECEIVED

FEB 23 1959

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

C.S. File 51/178 h

Map File M207 16

The survey is continued from the corner to Sections 5, 6, 7 and 8, T. 31 S., R. 9 W., W.M.

Find BTs and set 3/4" iron pipe and post from which:

- A Cedar 18" in Dia. brs. S 46° E 41.5 feet
- A Cedar 26" in Dia. brs. N 79° E 57.3 feet
(Not recorded in original notes.)
- A Fir 48" in Dia. brs. S 45° W 3.3 feet (now a snag)
- A Fir 30" in Dia. brs. N 30° W 8.6 feet
- A Cedar 12" in Dia. brs. N 25° E 63.3 feet (down) ✓

East on trial line between Sections 5 and 8, T. 31 S., R. 9 W.

2635.9 - Intersect south of the 1/4 Corner 26.7 feet. Find mound of stone and the stone marked 1/4. Set new post in mound from which:

- A Hemlock 18" in Dia. brs. N 25° E 26.4 Feet (gone)
- A Hemlock 16" in Dia. brs. S 15° E 6.9 Feet

New BT

- A Fir 21" in Dia. brs. N 33° E 49.7 Feet (Scribed) ✓

Thence:

S 89° 25' W on true line between Sections 5 and 8 from 1/4 Corner - a distance of: 2,635.9 Feet

Continuing East on trial line between Sections 5 and 8, T 31 S., R. 9 W from the 1/4 Section Corner.

2635.5 Feet - Intersect the Section line between Sections 4 and 5, 22.5 feet North of the Corner to Sections 4, 5, 8 and

9. Find original stone for corner in place from which:

- A Hemlock 18" in Dia. brs. N 25° E - 8.6 feet
- A Hemlock 21" in Dia. brs. N 78° W -29.4 feet
(BT tag on face) ✓

The Hemlock S 40° W is down. Scribing still visible.

Thence:

S 89° 54' W - between Sections 5 and 8, T. 31 S., R. 9 W. 2,635.5 to the 1/4 Section Corner.

FILED
RECORDED
FEB 13 1911

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

Thence from the corner to Sections 4, 5, 8 and 9,
T. 31 S., R. 9 W., W.M.

N 05°48' W on true line between Sections 4 and 5.

Follow along cutting line established for the Robert
Dollar Company.

At:

1327.9 Find squared post for the S 1/16 Corner --
Without chaining -- continue out the line to
the 1/4 Corner. Find scribing and BTs as per
U.S. Government notes.

Returning to the Corner Common to Sections 5, 6, 7,
and 8, I run:

North bet. 5 and 6 assuming this line will run to
the West. We run N 05°00' W on trial line.

At:

2554.4 feet Intersect West of the 1/4 Section Corner
187.9 feet. Find the fir marked for the 1/4 Section
Corner from which:

A Fir 18" in Dia. brs. N 61°E 5.5 feet

A Fir snag 18" in Dia. brs. N 34°W 42.0 feet ✓

The distance from Section Corner to 1/4 Corner on true line
will be 2561.3 feet. Then:

N 00° 52' W on true line between Sections 5 and 6.

At:

1280.7 feet set 3/4" iron pipe on Cedar post for the
S1/16 corner from which:

A Cedar 40" in Dia. brs. N 67°E 52.6 feet

A Hemlock 10" in Dia. brs. S 52°W - 10.4 feet ✓

Then without chaining run from the S 1/16 corner ✓
between Sections 5 and 6 to the S 1/16 between Sections 4
and 5. This being the boundary of the Cutting Contract
with the Coos Bay Timber Co.