

Section Corner: Sections 9 & 10 T27S, R2W

Found: G. L. O. Brass cap (1957)

W. Fir 17" dia., N 33°E, 42.9 ft.

S. Pine 20" dia., N 20°W, 40.9 ft.

D. Fir 12" dia., S 26½°W, 26.4 ft.

C. C. Sections 10, 15, & 16 T27S, R2W

Found: Ced. snag 16" dia., S 55°W, 33.5 ft.

Set: 2½" dia. Aluminum cap

D. Fir snag 14" dia., S 71°E, 38.5 ft.

W. Fir 12" dia., N 34°E, 39.1 ft.

West ¼ Corner Section 10 T27S, R2W

Found: G. L. O. Brass cap (1957)

Ced. snag 11" dia., N 40°W, 46.2 ft.

W. Fir snag 21" dia., S 75°W, 14.1 ft.

D. Fir 18" dia., S 56°E (down)

North ¼ Corner Section 10 Only T27S, R2W

Set: 2½" dia. Aluminum cap

Hem. 7" dia., S 08°E, 38.1 ft.

¼ Section Corner, Sections 10 & 11 T27S, R2W

Found: D. Fir snag 30" dia., N 13½°W, 12.1 ft.

Set: 2½" dia. Aluminum cap

Hem. 7" dia., N 31½°W, 27.3 ft.

W. Fir 7" dia., S 50°E, 38.6 ft.

South 1/16 between Sections 11 and 12 T27S, R2W

Set: 2½" dia. Aluminum cap

D. Fir 7" dia., N 76°W, 62.9 ft.

W. Fir 10" dia., N 40°E, 46.6 ft.

January 1965

FILED
RECEIVED

FEB 2 1965

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

