

Section Corner: Sections 1, 2, 11, 12

T28S, R3W

Found: 2½" Aluminum cap # 98

27" D. Fir, S 30° E, 28 ¼/10 ft; scribed S 12, T28S, R3W CS BT

Cut high stump above scribe

24" W. Fir, N 19½° E, 11 2/10 ft; scribed S 1, T28S, R3W CS BT

Cut high stump above scribe

10" W. Fir, S 21° W, 26 ft. ; scribed S 11, T28S, R3W CS BT

8" Yewood, N 05° W, 28 8/10 ft.; scribed S 2 CS BT

New BT's: 6" W. Fir, N 75½° E, 10 3/10 ft; scribed S 1 BT, Alum. tag REh287

8" Yew, S 57° E, 19 8/10 ft; scribed S 12 BT, Alum. tag REh287

121 ⊖

22 January 1965

¼ Section Corner: Sections 4 and 9

T28S, R3W

Found: 14" Ching., N 16° W, 24 ¼/10 ft.

16" Madrone, S 10° E, 16 1/10 ft.

New BT's: 36" Fir, S 72½° W, 70 1/10 ft.

47" Fir, N 29½° W, 71 9/10 ft.

Note: Proposed road will destroy original BT's

122 -

FILED
RECEIVED

FEB 2 1965

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

