

Renew $\frac{1}{4}$ S 36 $\frac{1}{4}$ T 255 R1W & R1E

Fd. B.T.s as follows -

Orig. 50" Fir N. $80\frac{1}{2}^{\circ}$ W. 28 $\frac{1}{4}$ ft.

Now STUMP - shows "T" scribe

1927 Resurvey 8" Fir S. 37° W. 30 $\frac{1}{4}$ ft.

Down - shows " $\frac{1}{4}$ S36 BT" on unhealed

Blaze - we find no trace of rock

called for - set 1" I.P. & Brass cap

Mkd. "COUNTY SURVEYOR'S OFFICE 1966

T255 R1W $\frac{1}{4}$ S36 | R1E" 14" in ground

& Build mound of stone 18" high.

Mkd. New B.T.s -

8" W. Fir S. 49° W. 12 $\frac{1}{2}$ ft.

Mkd. " $\frac{1}{4}$ S36 CS BT"

24" Hemlock S. 16° W. 18 $\frac{1}{2}$ ft.

Mkd. " $\frac{1}{4}$ S36 CS BT"

This cor. Lies on Right Bank
of of CANTON CREEK.

OCT 13, 1966

FILED
RECEIVED

URT
J.H.
D.W.

OCT 13 1966

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

0x69
R210R1E

C. S. File No. 52/30-25