

Renew Sec. Cor. <sup>510/511</sup> 515/514 T245 RIW

Fd. 16" x 10" x 10" Cor. Stone MKd. with  
2 Notches on N. & 4 Notches on S.

Firmly set. & O.B.T.s 25 follows -

Orig. 16" Now 24" Pine N. 39° E. 21 <sup>1</sup>/<sub>2</sub> ft.

Record calls for Fir N. 36° E. - 2 live

scribe visible on unhealed blaze.

Orig. 10" Now 13" Fir S. 29 <sup>1</sup>/<sub>2</sub>° E. 17 <sup>8</sup>/<sub>16</sub> ft.

Record Bearing S. 34° E. - 2 live - shows scar.

Orig. 24" Now 31" Fir S. 5° W. 70° ft.

Record Bearing. S. 2° W. - 2 live - shows scar.

Orig. 12" ? Now 24" Pine N. 51° W. 32 <sup>3</sup>/<sub>4</sub> ft.

Record Bearing. - N. 58 <sup>1</sup>/<sub>2</sub>° W. Now 5 N 29

scribe visible on unhealed blaze.

Set 1" I.P. & Brass cap MKd. "COUNTY

SURVEYOR'S OFFICE 1969 T245

<sup>510/511</sup> 515/514 RIW "Reset Rock along side - New O.B.T.s -

8" Hemlock N. 40° W. 16° ft.

Mkd. "T245 RIW 510 CS BT"

7" Hemlock S. 54° W. 24 <sup>8</sup>/<sub>16</sub> ft.

Mkd. "T245 RIW 515 CS BT"

16" Fir N. 49° E. 11 <sup>1</sup>/<sub>2</sub> ft.

Mkd. "T245 RIW 511 CS BT"

This cor. lies on steep Easterly slope

Oct. 12, 1967

~~W.B.~~ W.B. Tray

V.R.T.

J.H.

C. S. File No. <sup>V.P.</sup> 52/92-59