

Renew Sec. Cor. $\frac{56}{57} | \frac{55}{58}$ T265 RIW

Fd. Cor. Stone in place with "X" on
Top & 5 Notches on S. & E. edges -
Q.B.T.s as follows -

Orig. 6" Now 14" FIR N. 33° E, 57 $\frac{1}{2}$ ft.
alive - we open & find " \ 5" scribe
& Reverse -

Orig. 18" Now 40" FIR S. $4\frac{1}{2}^{\circ}$ W, 71 $\frac{3}{4}$ ft.
alive - shows good scar - we tag.

Orig. 40" Now 60" FIR S. 53° E, 83 $\frac{1}{2}$ ft.
alive - shows good scar - we tag -
possible Remains of NW Q.B.T. - Down

& Badly decayed - at cor. point in
place of old stone, set 1" I.P. &

Brass cap MKd. "COUNTY SURVEYORS
OFFICE 1970 T265 $\frac{56}{57} | \frac{55}{58}$ RIW"

Reset old stone alongside - MK. New
B.T.s -

18" D. FIR N. 49° W, 14 $\frac{1}{2}$ ft.

Mkd. "T265 RIW S 6 CS BT"

12" D. FIR N. 17° E, 13 $\frac{1}{2}$ ft.

Mkd. "T265 RIW S 5 CS BT"

14" D. FIR S. 67° E, 6 $\frac{1}{2}$ ft.

Mkd. "T265 RIW S 8 CS BT"

(CONT. OVER)

*47

C. S. File No. 52/77-29
D. H. W. 19.

CONT.

6" D. FIR S. 20' W. 18' 2" ft.
MKD. "57CSBT"

This COR. Lies on Very Gentle
Almost Flat Easterly Slope
Approx. 1400 ft. East of Burnt
Creek Access Road #2644.

March 6, 1970

V.R.T.
J.E.H.
V.D.A.

V.R.T.

0.5
5-20-70