

Corners renewed.

T. 30 S., R. 3 W.

Closing Corner to Sections 5 + 9

Found 20" Fir N. 36° 30' E. 17.8 ft. (Dead)

16" Fir N. 72° W. 14.5 ft. (Dead)

Drive ½" I. Pipe for Corner.

Scrib 32" Fir N. 32° 30' E. 75.6' (Dead but Sound)

+ ✓ No other trees available, April 1952

¼ Corner between Sec. 4 + 9

Placed by running line East + West.

Drive ¾" I. Pipe for Corner.

Scribe 16" Fir N. 53° E. 13.3 ft.

+ ✓ 16" Fir S. 4° 45' W. 25.8 ft. April 1952.

Closing Corner to Sections 4 + 9

Placed by measurements North + South.

Drive ½" I. Pipe for Corner.

Scribe 10" Fir N. 33° E. 37.8 ft.

+ ✓ 14" Maple S. 31° 35' E. 27.4 ft. April 1952.

REGISTERED  
OREGON  
LAND SURVEYOR

Geo. J. Wenderoth,

MARCH 10, 1944  
George J. Wenderoth  
5

FILED  
RECEIVED

FEB 1 1963

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

S. File No. 52/138-53