

Sec. Cor. for Secs. 17, 18, 19 & 20, T23S, R3W, WM

New trees marked:

6" Alder	brs.	N 04° E	2.0 ft.,	marked	S17BT
6" Alder	"	N 75° W	14.2 ft.	"	S18BT
8" Alder	"	S 45° W	14.9 ft.	"	S19BT
6" Alder	"	S 54° E	21.5 ft.	"	S20BT

#19-

Placed steel axle in ground at location of old corner, as located and preserved by John F. Woodard.

.....

1/4 Cor. between Secs. 20 & 21, T23S, R3W, WM

Stake in stump on Hemlock tree previously marked for corner; scribing visible in said stump.

#20-

Marked new trees:

16" Hemlock	brs.	N 75° E	22.5 ft.,	marked	1/4 S BT
8" Cedar	"	S 73° E	90.0 ft.,	"	1/4 S BT

No other tree available.

.....

1/4 Cor. between Secs. 21 & 22, T23S, R3W, WM

New bearing trees:

18" Douglas Fir	brs.	S 11° E	7.8 ft.,	marked	1/4 S BT
(original SE bearing tree cut, now 38" stump)					
10" Incense Cedar	brs.	N 41° W	39.2 ft.		

#21

This corner is 100 feet East of rock quarry and approximately 60 ft. above logging road on North side.

.....

Sec. Cor. for Secs. 27 & 28, 21 & 22, T23S, R3W, WM

Placed by J. F. Woodard at location of old corner. Found by tearing apart old stump in which scribe marks were visible, and which John F. Woodard showed to me, and after examining same, remains of scribing were still visible.

Marked new bearing trees:

20" Hemlock	brs.	S 78° E	18.2 ft.,	marked	S27BT
18" Hemlock	"	N 85° E	16.2 ft.,	"	S22BT
60" Cedar	"	S 65° W	12.0 ft.,	"	S28BT
20" Hemlock	"	N 85° W	28.9 ft.,	"	S21BT

.....

Cor. for Secs. 28, 29, 20 & 21, T23S, R3W, WM

Found stump marked for corner with parts of scribe plainly visible. Remarkd trees as follows:

24" Douglas Fir	brs.	S 34° W	18.5 ft.
18" Douglas Fir	"	S 41° E	28.0 ft.
20" Douglas Fir	"	N 33° E	24.0 ft.
24" Fir	"	N 86° W	23.0 ft.

.....

Gilbert A. Gardner

June 2, 1954
J. F. Woodard

CS 53/1-17