

The 1/4 sec. cor. bet. secs. 18 Tp 20 S R 5 W and sec. 13 To 20 SR 6 W
 At this corner I found the bearing tree described as a fir 24 ins.
 diam. bearing S 24° E 12 links in good shape, the post and
 Southwest bearing tree were gone. I reestablish this corner by
 setting a post (cedar) from which var 22° E
 a fir 40 ins. diam. marked CSBT 1/4 S. brs S 24° E 12 links dist.
 a maple 24" " " " " " " N 26° W 39 " " "

one of the
BTS

July 16, 1934

Present J.J. Hooker & Charles Long
 Earl G. Muir Surveyor
 Recorded by G. H. Waggoner

Corner to secs. 17, 18, 19 & 20 Tp 20 S R 5 W
 At this corner I find no evidence remaining except the remnants
 of the bearing tree, a fir 70 ins. diam. bearing S 35° E 103
 links with the original marks plainly showing in the bark.
 Set new cedar post 4x4" 4 feet long from which
 The stub of the original bearing tree a fir 70 ins diam brs
 S 35° E 103 lks. dist.

See Book 205 R 5 W
Page 167

A fir 22 ins diam marked T 20 SR 5 W S20 CSBT brs. S 35° E 31 lks. dist.
 " " 14 " " " T 20 SR 5 W S19 CSBT " S 60° 30' W 13 lks d.
 " " 22 " " " T 20 SR 5 W S18 " " " N 67° W 39 lks. dist.
 " " 18 " " " T 20 SR 5 W S17 " " " N 48° 30' E 28 lks. d.

July 16, 1934

Earl G. Muir Surveyor
 Recorded by G. H. Waggoner

The 1/4 sec. cor. bet. secs. 18 & 19 Tp 20 S R 5 W
 In retracing this line bet. secs. 18 & 19 I find no trace of the
 1/4 section corner. I reestablish this corner by setting a post
 3x3"x4' by proportionate measurements 40.05 chs. N 89° 34' W
 from the corner of section 17, 18, 19 & 20. The length and bearing
 of the line between secs. 18 & 19 is N 89° 34' W 81.27 chains.
 Mark bearing trees as follows
 a fir 24 ins diam marked 1/4 S CSBT brs S 62° E 14 links dist.
 a maple 12" " " " " " N 4° E 56

July 12, 1934

Earl G. Muir Surveyor
 Recorded by G. H. Waggoner

The 1/4 sec. cor. bet. secs. 33 & 34 Tp 17 S R 7 W W.M.
 Being unable to find any trace of the 1/4 sec. cor. bet. secs. 33 & 34
 Tp 20 S R 5 W I retrace the line between secs. 33 & 34 S 00° 5'
 E 79.95 chains and at 39.97 1/2 chains set a cedar post for 1/4 sec.
 cor. from which var. 22
 a fir 20 ins. diam. marked 1/4 S CSBT brs. S 87° E 60 links dist.
 a fir 16 " " " " " " N 40 1/2° W 32 " "
 40.6 " "

July 13, 1934

Present Francis Jepson, Melvin Innman and Albert Lake
 Earl G. Muir Recorded by G.H. Waggoner

12 COPIES