

REN.

T 19 S R 10 W

COR.
SECS.

27 | 26
34 | 35

FD. FIR SNAQ N 59° W 5³ FT. -

PREVIOUSLY OPENED - GOOD SCRIBING

VISIBLE "T 19 S R 10 W 27"

FD. DOUG. FIR (NOW 42" DIAM.)

N 58° E 35⁶ FT. - SHOWS GOOD SCARS.

FD. DOUG. FIR (NOW 36" DIAM.)

S 64° W 11⁹ FT. - SHOWS GOOD SCARS.

FD. DOUG. FIR (NOW 36" DIAM.)

S 7° E (NOT 57° E) 12⁵ FT. -

SHOWS GOOD SCARS.

AT COR. SET IRON PIPE WITH
BRASS CAP MKD. "COUNTY SURVEYOR'S
OFFICE 1964 T 19 S R 10 W S 27 | S 26
S 34 | S 35"

BLAZE & RESCRIBE:

36" DOUG. FIR S 64° W 11⁹ FT.

MKD. "T 19 S R 10 W S 34 CS BT"

36" DOUG. FIR S 7° E 12⁵ FT.

MKD. "T 19 S R 10 W S 35 CS BT"

42" DOUG. FIR N 58° E 35⁶ FT.

MKD. "T 19 S R 10 W S 26 CS BT"

BLAZE & SCRIBE:

10" HEMLOCK N 29° E 90² FT.

MKD. "T 19 S R 10 W S 26 CS BT"

+X Milo C. Godfrey

SEPT. 24, 1964

M.C.
U.S. File No. 53/66