

Review Sec. Cor. ^{53/52} 510/511 T205 R11W

Fd. COR. STONE in place MKd with
5 Notches on S. & 2 Notches on E.
edges & O.B.T.s as MKd. by F.W. Page
in 1916 when Surveying H.E.S. #190
10" Now 19" FIR S. $36\frac{1}{2}^{\circ}$ E 25' ft.
alive - shows good scar wetag.

10" Now 25" FIR N. $19\frac{1}{2}^{\circ}$ W, 10' ft.
alive shows good scar - wetag.

O.B.T.s to NE & SW Down & Decaying.

at cor. point in place of stone
set 1" I.P. & Brass cap MKd. "COUNTY

SURVEYOR'S OFFICE 1970 T205

^{53/52} 510/511 R11W" & MK. new BT. out
of area to be cleared.

36" D. FIR S. 88° W, 59' ft.
MKd. "T205 R11W 510 CS BT"

This COR. Lies on NW. slope
approx 30 ft. S. & 40 ft. W. of
Top of Spur Ridge sloping
NW. — No Trace of orig. older
B.T.s Fd.

April 1, 1970

V.R.T.
J.G.H.

V.R.T. Ray
#88

FOR U.S.F.S. DIV. N.W. 2
C. S. File No. 52/66-95