


PUBLIC LAND CORNERS

SPRINGFIELD
 SURVEY FILE

Weyerhaeuser Timber Company
 Springfield Branch
 TOWNSHIP 22S RANGE 4W
 SECTION 4 CORNER SW
 COUNTY DOUGLAS OREGON



GLO SURVEY RECORD

DATE: 1855
 CORNER Post

PRESENT CONDITION - (DESCRIBE FULLY - USE PAGE 2 IF NEEDED FOR EXPLANATION.)

GONE

ACCESSORIES:

	BEARING-	LINKS-	FEET-	
60" Fir	N 37° E	72	47.5	60" Fir stump
4" Fir	S 50° E	95	62.7	No Trace
50" Fir	S 81° W	47	31.0	60" Fir - Probably originally bark scribed. Now bark scribed by Douglas Co. 1958.
21" Fir	N 48° W	64	42.2	26" Fir - Orig. scribing visible
(An 1884 survey found all four original BT's)				

COUNTY DOUGLAS SURVEY RECORD
 DATE: 1958

PRESENT CONDITION:

Found

Found 3/4" iron pipe				
16" White Fir	N 35° E	59.1'	16 "	White Fir Scribing S 4 CS BT
18" White Fir	S 50° E	22.1'		18" White Fir - Scribed S9 CS BT
60" Red Fir	S 80° W	35.0		60" Douglas Fir - Bark scribed S 8 CS Bt
Scribed Original NW BT -	N 48° W			26" Fir - Scribed S 5 CS BT

CORNER SET: 3/4" Iron Pipe as found by Douglas County MAG. DECL.: 20°
 Survey

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:

BEARING-	FEET-	SURVEY-	
N 37° E	47.5	GLO	to center of stump
S 80° W	37.6	GLO	to center of tree
N 48° W	42.2	GLO	to center of tree
S 50° E	62.7	County	to center of tree
S 80° E	31.0	County	to scribed face
S 80° W	31.5	County	to bark scribing
N 48° W	42.2	County	to center of tree

PAGE 1

ACCESSORIES ADDED THIS DATE:

MAGNETIC DECLINATION 20°

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
16" White Fir	S 50° E	21.3	County	x	x	
60" fir	S 80° W	33.1	County	x	x	
26" Fir	N 48° W	41.4	County	x	x	
14" White Fir	N 34° E	58.6	County	x	x	

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: Salal, Fern, Oceanspray and Hazel

(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)

SLOPE FACES (GIVE BEARING IN DEGREES) N 45° E ON MINUS (-) 48 %

NORTH: -3% 25' small ravine C - East

SOUTH: +38% Logged on West - Virgin timber to East will be logged Summer 1959

EAST: -28% 120' CR C N42E - logged to North - Virgin Timber to South to be logged Summer, 1959

WEST: +22% Logged to North and South

WORK DONE FOR W. T. CO.:

FIELD NOTES IN BOOK:

BY: Allen McCreaney DATE: June 9, 1959
 ENGINEER - SURVEYOR

UNDER THE SUPERVISION OF:

ASSISTED BY: ROBERT BARTA

COPIES SENT TO:

SEAL PAGE 3

CS 53/105-2