


PUBLIC LAND CORNERS

WEYERHAEUSER COMPANY
SPRINGFIELD BRANCH

TOWNSHIP 22 S RANGE 4 W
SECTION 10 CORNER NW
COUNTY Douglas OREGON



ACCESSORIES ADDED THIS DATE:

MAGNETIC DECLINATION 20°

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
12" Chinquapin	N 75° E	28.7	---	X	X	---
16" Incense Cedar	S 73° E	25.1	1903	X	X	---
None						
None						

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: Ocean spray - edge of logging

(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)

SLOPE FACES (GIVE BEARING IN DEGREES) S 40° W ON MINUS (-) 20 %

NORTH: + 20%

SOUTH: - 20%

EAST: + 10%

WEST: Level

WORK DONE FOR W. CO.

FIELD NOTES IN BOOK:

BY: Allen M. Chimes DATE: August 22, 1963

~~WYERHAEUSER SURVEYOR~~
LAND AGENT

ASSISTED BY:

UNDER THE SUPERVISION OF:

COPIES SENT TO:

SEAL PAGE 3

GLO SURVEY RECORD

DATE: 1855
CORNER Post

PRESENT CONDITION - (DESCRIBE FULLY -
USE PAGE 2 IF NEEDED FOR EXPLANATION)

Gone

ACCESSORIES:

	BEARING-	LINKS-	FEET-	
50" Fir	N 47° E	32	21.1	60" down Fir - Scribing not visible
30" Fir	S 11° E	22	14.5	No trace
15" Fir	S 42° W	28	18.5	36" White Fir - face healed over
18" Fir	N 6° W	94	62.0	38" Fir stump - face healed over
GLO retracement 1903:				
8" Cedar	S 73½° E	39	25.7	16" Inc. Cedar - scribing visible

SURVEY RECORD

DATE:

PRESENT CONDITION:

Found in field: C S Brass cap dated 1962
and 4 BIS scribed "CSBT"

6" White Fir - plate reads "S 11 W - 40.3' "
10" White Fir - " " "N 65 W - 8.1' "
12" White Fir - " " "N 42 E - 50.0' "
10" White Fir - " " "S 35 E - 6.4' "

CORNER SET: CS Brass cap as found

MAG. DECL.: 20°

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:

BEARING-	FEET-	SURVEY -	
N 47° E	21.1	GLO	
S 42° W	18.5	"	Distance is to root hole
N 6° W	62.0	"	Distance to face
S 72° E	24.8	GLO-1903	" " "
N 10° E	39.4	C S	" " "
S 63° E	8.0	"	" " "
S 41° W	46.0	"	" " "
N 38° W	5.7	"	" " "

PAGE 1

CS 53/105-6