


PUBLIC LAND CORNERS

WEYERHAEUSER COMPANY
SPRINGFIELD BRANCH

TOWNSHIP 22 S RANGE 4 W
SECTION 10 CORNER S 1/4
COUNTY Douglas OREGON



GLO SURVEY RECORD				PRESENT CONDITION - (DESCRIBE FULLY - USE PAGE 2 IF NEEDED FOR EXPLANATION.)	
DATE: 1884				No trace	
CORNER Post					
ACCESSORIES:					
12" maple	BEARING- S 2° E	LINKS- 61	FEET- 40.3	24" maple; face opened; scribed "1/4S" visible.	
40" Fir	N 39° N	35	23.1	48" fir, recent windfall; apparently bark scribing burned off; only tree in proper position	
SURVEY RECORD				PRESENT CONDITION:	
DATE: 1955					
Squared stake set by Clyde Randall for W. A. Woodard Co. and marked 1/4 S				Stake remains; is above ground about 1 foot and contains hub tack.	

CORNER SET: _____ MAG. DECL.: 20°

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:			
BEARING-	FEET-	SURVEY-	
S 8° E	43.0	1884	Measured to center of tree

ACCESSORIES ADDED THIS DATE: _____ MAGNETIC DECLINATION 20°

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
20" Cedar	N 29° E	56.2	--	x	x	--
24" Maple	S 8° E	40.2	x	x	x	--

IDENTIFIED ON PHOTO: _____

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: Salal and sword fern

(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)

SLOPE FACES (GIVE BEARING IN DEGREES) N 20° W 7 %

NORTH: + 5%; 40' to spring branch bearing East
uncut O.G. Doug. fir East and West

SOUTH: + 27%; uncut O.G. Doug. fir East and West

EAST: + 22%

WEST: + 26%; 12' to spring branch bearing N 20° W 200 feet to
sharp curve in logging road

WORK DONE FOR W. CO. _____ FIELD NOTES IN BOOK: _____

BY: William L. Hilt DATE: 1-18-63
~~ENGINEER SURVEYOR~~

ASSISTED BY: Ron Kaufman & Ed Ware,
(BLM)

COPIES SENT TO: _____

UNDER THE SUPERVISION OF: _____

CS 53 / 105-7