


SPRINGFIELD SURVEY FILE

PUBLIC LAND CORNERS

WEYERHAEUSER COMPANY  
SPRINGFIELD BRANCH

TOWNSHIP 22S RANGE 4W  
SECTION 17 CORNER SW  
COUNTY Douglas OREGON



GLO SURVEY RECORD  
DATE: 1856  
CORNER Stake  
PRESENT CONDITION - (DESCRIBE FULLY - USE PAGE 2 IF NEEDED FOR EXPLANATION.)  
Stake Gone

ACCESSORIES:

	BEARING-	LINKS-	FEET-	
18" W. Oak	S 75° W	149	98.3	Land cleared; no evidence.
60" W. Oak	S 45° E	122	80.5	50" Stump; bottom of upper face shows in stump cut; cut below scribing.
20" W. Oak	N 63° W	74	48.8	Found remains oak stump only.
6" W. Oak	N 10° E	48	31.7	Land cleared; no evidence.

Douglas County SURVEY RECORD  
DATE: 9-18-28  
Set 1" x 6' G. I. pipe 5 1/2' in ground Found 3/4" iron rod; extends 6" above ground.  
60" W. Oak S 45° E 122 lks. (80.5) 50" Oak stump as above, stump decayed in several inches.  
(O. B.T. of 1856 remarked)  
12" Fir N 87 3/4° E 47 lks. (31') 22" Stump, base blaze shows; not opened.  
30" Fir N 44 1/2° W 30 lks. (19.8) 36" Stump cut low  
14" B. Oak S 63 1/2° W 29 lks. (19.1) 26" B. Oak; faces show plainly; not opened  
30" W. Oak (O.B.T.) N 68° W 74 lks (48.8) Stub of remains old stump found N 63° W  
CORNER SET: (Measured from 3/4" I. Rod as found) MAG. DECL.: 20°

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:

BEARING	FEET	SURVEY
S 45° E	81.4	1856 & 1928 Measure from I. Rod to old face in stump cut; chopped out but cut below scribing.
N 63° W	48.4	1856 (County record calls N 68° W but no evidence found at this bearing and dist.)
N 88° E	34.0	1928 Measure from I. Rod to scar in stump cut.
N 31° W	19.4	1928 " " " " center stump. This is only stump near call distance and bearing.
S 64° W	16.0	1928 Measure to center of tree.

ACCESSORIES ADDED THIS DATE:

MAGNETIC DECLINATION 20°

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
26" B. Oak (1928 County B.T.)	S 64° W	14.9	-	X	X	-
12" W. Oak	S 63° E	20.1	-	X	X	-
10" W. Oak	N 85° E	50.2	-	X	X	-
36" Fir Stump	N 31° W	19.0	-	X	X	-

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: Grass Pasture  
(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)  
SLOPE FACES (GIVE BEARING IN DEGREES) North ON MINUS (-) 35 %

FROM CORNER 1  
NORTH: -35%; about 60' to creek bottom flat and about 100' total distance to creek bearing SW. Partially cleared pasture.  
SOUTH: +12%; 6' to centerline Jackson Road; partially cleared pasture.  
EAST: +10%; 15' to center line Jackson Road  
WEST: -15%; partially cleared pasture.

WORK DONE FOR W. CO.

FIELD NOTES IN BOOK:

BY: William D. Hill DATE: July 5, 1962  
ENGINEER-SURVEYOR  
Land Agent

UNDER THE SUPERVISION OF:

ASSISTED BY: (None)

COPIES SENT TO:

CS 53/105-16