

SPRINGFIELD SURVEY FILE


PUBLIC LAND CORNERS

Weyerhaeuser Timber Company
 Springfield Branch

TOWNSHIP 22 S RANGE 4 W

SECTION 34 CORNER NW 1/16

COUNTY Douglas OREGON



ACCESSORIES ADDED THIS DATE:

MAGNETIC DECLINATION 20°

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
10" W. Oak	N 40° E	10.9	CSBT	X	X	
11" W. Oak	N 67° W	28.5	CSBT	X	X	

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: Grass

(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)

SLOPE FACES (GIVE BEARING IN DEGREES) S 30° E ON MINUS (-) 20 %

FROM CORNER -

NORTH: 47% 2nd Growth

SOUTH: - 22% Open Field

EAST: -12% " "

WEST: 24% W. Oak Brush

WORK DONE FOR W. T. CO.:

FIELD NOTES IN BOOK:

BY: William L. Hilt DATE: Jan. 5, 1961
 LAND AGENT

ASSISTED BY: Robert Barta

UNDER THE SUPERVISION OF:

COPIES SENT TO:

SEAL PAGE 3

GLO SURVEY RECORD

PRESENT CONDITION - (DESCRIBE FULLY - USE PAGE 2 IF NEEDED FOR EXPLANATION.)

DATE:

CORNER

ACCESSORIES:

BEARING-	LINKS-	FEET-

SURVEY RECORD

PRESENT CONDITION:

DATE:

Found in field:

10" W. Oak N40° E 11.1' Scribing

11" W. Oak N67° W 28.7' Healed

faces

CORNER SET: Found Cedar stake in fence line MAG. DECL.:

scribed "1/16 S" and mound of stone

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:

BEARING-	FEET-	SURVEY-

CS 53 / 105 - 31