


SPRINGFIELD
SURVEY FILE

PUBLIC LAND CORNERS

WEYERHAEUSER TIMBER COMPANY
 SPRINGFIELD BRANCH



TOWNSHIP 23 S RANGE 3 W
 SECTION 28 CORNER S 1/4
 COUNTY DOUGLAS OREGON

GLO SURVEY RECORD		PRESENT CONDITION - (DESCRIBE FULLY - USE PAGE 2 IF NEEDED FOR EXPLANATION.)	
DATE:	1882		
CORNER	5" DOGWOOD		GONE
ACCESSORIES:			
	BEARING-	LINKS-	FEET-
10" Dogwood	South	25	Gone
6" Dogwood	N 10° E	8	Gone
G.A. Gardner SURVEY RECORD			
DATE:	1953		
	12" x 12" x 20" stone and 1" I.P.		20" dead Yew scribed 1/4S B.T. BLM tag
	8" Dead Yew N 36° E 25.4"		18" Yew scribed 1/4S B.T. BLM tag
	10" Yew S 80° E 140.7'		

CORNER SET: _____ MAG. DECL.: _____

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:			
BEARING-	FEET-	SURVEY-	
N 36° E	25.7	Gardner	20" Dead yew
S 83° E	140.7	Gardner	18" Yew

ACCESSORIES ADDED THIS DATE:

MAGNETIC DECLINATION 20°

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
44" Fir Stump	N 75° E	27.0		x	x	
36" Fir Stump	S 40° W	30.8		x	x	

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: Logged approximately 6 years ago, burnt
 (USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)
 SLOPE FACES (GIVE BEARING IN DEGREES) S 62° W ON MINUS (-) 35 %

FROM CORNER 1

NORTH: + 7% for 50'

SOUTH: - 17% for 50'

EAST: + 28% for 75' to Rd. #300 off Skyline Road

WEST: - 30% for 70' swale course south

WORK DONE FOR W. T. CO.:

FIELD NOTES IN BOOK: _____

BY: M. D. HALE DATE: APRIL 1, 1959
ENGINEER - SURVEYOR

UNDER THE SUPERVISION OF:

ASSISTED BY: W.W. DIXON

COPIES SENT TO: _____

CS 53/107-5

91