


SPRINGFIELD  
**SURVEY FILE**

# PUBLIC LAND CORNERS

WEYERHAEUSER COMPANY  
 SPRINGFIELD BRANCH

TOWNSHIP 23 S RANGE 3 W  
 SECTION 31 CORNER S1  
 COUNTY Douglas OREGON



*Scale #38*

| <b>GLO SURVEY RECORD</b>  | <b>PRESENT CONDITION - (DESCRIBE FULLY - USE PAGE 2 IF NEEDED FOR EXPLANATION.)</b> |           |       |                |                   |           |                |                   |           |  |  |  |  |  |  |  |
|---|---|-----------|-------|----------------|-------------------|-----------|----------------|-------------------|-----------|--|--|--|--|--|--|--|
| DATE: <u>1950</u>   |   |           |       |                |                   |           |                |                   |           |  |  |  |  |  |  |  |
| CORNER <u>Iron post 3" by 1" &amp; brass cap</u>  | <u>Iron post &amp; cap present</u>  |           |       |                |                   |           |                |                   |           |  |  |  |  |  |  |  |
| <b>ACCESSORIES:</b>   |   |           |       |                |                   |           |                |                   |           |  |  |  |  |  |  |  |
| <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>BEARING-</th> <th>LINKS-</th> <th>FEET-</th> </tr> </thead> <tbody> <tr> <td><u>10" Yew</u></td> <td><u>N 64 45' W</u></td> <td><u>14</u></td> </tr> <tr> <td><u>10" Yew</u></td> <td><u>S 16 1/2 E</u></td> <td><u>19</u></td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> <tr> <td> </td> <td> </td> <td> </td> </tr> </tbody> </table> | BEARING-  | LINKS-    | FEET- | <u>10" Yew</u> | <u>N 64 45' W</u> | <u>14</u> | <u>10" Yew</u> | <u>S 16 1/2 E</u> | <u>19</u> |  |  |  |  |  |  | <u>10" Yew scribing legible</u><br><u>10" Hemlock scribing legible</u> |
| BEARING-  | LINKS-  | FEET-     |       |                |                   |           |                |                   |           |  |  |  |  |  |  |  |
| <u>10" Yew</u>  | <u>N 64 45' W</u>   | <u>14</u> |       |                |                   |           |                |                   |           |  |  |  |  |  |  |  |
| <u>10" Yew</u>  | <u>S 16 1/2 E</u>   | <u>19</u> |       |                |                   |           |                |                   |           |  |  |  |  |  |  |  |
|   |   |           |       |                |                   |           |                |                   |           |  |  |  |  |  |  |  |
|   |   |           |       |                |                   |           |                |                   |           |  |  |  |  |  |  |  |
| <b>SURVEY RECORD</b>  | <b>PRESENT CONDITION:</b>   |           |       |                |                   |           |                |                   |           |  |  |  |  |  |  |  |
| DATE: _____   | _____   |           |       |                |                   |           |                |                   |           |  |  |  |  |  |  |  |

CORNER SET: \_\_\_\_\_ MAG. DECL.: \_\_\_\_\_

**BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:**

| BEARING-          | FEET-       | SURVEY -        |
|-------------------|-------------|-----------------|
| <u>N 64 45' W</u> | <u>9.2</u>  | <u>G. I. O.</u> |
| <u>S 16 1/2 E</u> | <u>12.5</u> | <u>G. I. O.</u> |
|                   |             |                 |
|                   |             |                 |

ACCESSORIES ADDED THIS DATE: \_\_\_\_\_

MAGNETIC DECLINATION: 20°

|                     | BEARING       | FEET        | ORIG. B.T. | "W" NAIL | PLATE    | BRASS DISC |
|---------------------|---------------|-------------|------------|----------|----------|------------|
| <u>17" Yew</u>      | <u>N 40 W</u> | <u>26.1</u> | <u>--</u>  | <u>X</u> | <u>X</u> | <u>--</u>  |
| <u>72" Fir Snag</u> | <u>S 42 W</u> | <u>5.3</u>  | <u>--</u>  | <u>X</u> | <u>X</u> | <u>--</u>  |
|                     |               |             |            |          |          |            |

IDENTIFIED ON PHOTO: \_\_\_\_\_

**INFORMATION ON LOCATION OF CORNER AS NOW SET:**

GROUND COVER: Open Timber to the South

(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)

SLOPE FACES (GIVE BEARING IN DEGREES) S 30 W ON MINUS (-) - 65 %

NORTH: ↓ 55% for 150' breaks to gentle slope

SOUTH: - 80% for 100" to small stream

EAST: ↓ 25% for 100" breaks to gentle slope

WEST: -50% for 75' to small stream

WORK DONE FOR W. CO. \_\_\_\_\_

FIELD NOTES IN BOOK: \_\_\_\_\_

By: Bruce Malcom DATE: January 17, 1962

**ENGINEER SURVEYOR**  
 Assistant Forester

ASSISTED BY: Bob Duncan

UNDER THE SUPERVISION OF: \_\_\_\_\_

COPIES SENT TO: \_\_\_\_\_

SEAL

*CS 53/107-9*

*02*