


PUBLIC LAND CORNERS

SPRINGFIELD
 SURVEY FILE

WEYERHAEUSER TIMBER COMPANY
 SPRINGFIELD BRANCH

TOWNSHIP 23 S RANGE 4 W
 SECTION 12 CORNER NW
 COUNTY Douglas OREGON



ACCESSORIES ADDED THIS DATE:

MAGNETIC DECLINATION 20°

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
12" Fir	N 24 E	39.5	----	X	X	----
32" Fir	S 69 E	15.1	CS	X	X	----
22" Fir	S 50 W	41.5	CS	X	X	----
36" Fir	N 79 W	8.7	CS	X	X	----

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: Grass, stumps
 (USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)
 SLOPE FACES (GIVE BEARING IN DEGREES) S 75 W ON MINUS (-) 23 %

NORTH: +11% Logged
 SOUTH: -13% Logged to East, Timber to West
 EAST: + 5% Logged
 WEST: -22% Logged to North, Timber to South

FROM CORNER 1

GLO SURVEY RECORD

DATE: 1855 ?

CORNER Post

ACCESSORIES:

	BEARING-	LINKS-	FEET-	
18" Black Oak	S 8 W	455	300.3	Gone
24" White Oak	S 26 E	617	407.2	Found remains of Oak moved by logging
24" White Oak	N 4 W	960	623.6	" " " " " " " "
74" Fir	N 2 1/2 E		6.6	Gone

County SURVEY RECORD DATE: 1940

PRESENT CONDITION:

Surveyed by Thiel-
 Set stone 24"x16"x12" marked CS

Found with X on top and CS on southside

10" Fir	N 63 E	30.7	12"x3" Fir stub -scribing visible
30" Fir	N 80 W	9.6	32" Fir - Faces healed over
20" Fir	S 51 W	42.0	22" Fir - " " " "
28" Fir	S 66 E	15.8	36" Fir - " " " "

CORNER SET: Stone as found MAG. DECL.: 20°

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:

BEARING-	FEET-	SURVEY-	
N 62 E	31.0	CS	Distance measured to face.
N 80 W	9.6	"	" " " "
S 51 W	42.0	"	" " " "
S 68 E	15.8	"	" " " "

PAGE 1

WORK DONE FOR W. T. CO.:

FIELD NOTES IN BOOK:

BY: Allen M. Cheney DATE: 3/2/60
~~ENGINEER - SURVEYOR~~

UNDER THE SUPERVISION OF:

ASSISTED BY: Robert Barta

COPIES SENT TO:

SEAL

PAGE 3

CS 53/108-2