SPRINGFIELD SURVEY FILE

PUBLIC LAND CORNERS

WEYERHAEUSER COMPANY
SPRINGFIELD BRANCH

TOWNSHIP 23 S RANGE 4 W

SECTION 36 CORNER SE

COUNTY Douglas OREGON



GLO SURVEY RECORD

DATE: 1950

CORNER Brass Cap

PRESENT CONDITION – (DESCRIBE FULLY – USE PAGE 2 IF NEEDED FOR EXPLANATION.)

Found in mound of Stone

ACCESSORIES:

	BEARING–	LINKS–	FEET–	
9" Cedar	N 32 3/4 W	101	66.7	12" Cedar - Scribing Visible
36" Fir	S 77 1/4 W	182		40" Fir Stump - Scribing Visible

SURVEY RECORD

DATE:

PRESENT CONDITION:

CORNER SET: Brass cap as set by GLO 1950 MAG. DECL.: 20°

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:

BEARING–	FEET–	SURVEY–	
N 30 W	64.8	1950	Distance to face
S 79 W	118.3	"	" "

PAGE 1

ACCESSORIES ADDED THIS DATE:

MAGNETIC DECLINATION 20°

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
12" Cedar	N 30 W	64.6	1950	X	X	--
54" Fir Stump	S 51 W	29.0	--	X	X	--

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: 5-10 yr. Reproduction

(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)

SLOPE FACES (GIVE BEARING IN DEGREES) S 60 E ON MINUS (–) 20 %

FROM CORNER –

NORTH: + 5% Logged-Reproduction

SOUTH: - 10% " "

EAST: - 20% " "

WEST: + 20% " "

WORK DONE FOR W. CO.

FIELD NOTES IN BOOK:

BY: Glen McChesney DATE: 6/6/61

~~ENGINEER – SURVEYOR~~ Land Agent

ASSISTED BY: Bruce Malcom

COPIES SENT TO:

UNDER THE SUPERVISION OF:

SEAL

PAGE 3

CS 53/108-13