


PUBLIC LAND CORNERS

SPRINGFIELD
SURVEY FILE

WEYERHAEUSER COMPANY
SPRINGFIELD BRANCH

TOWNSHIP 23 S RANGE 4 W
SECTION 36 CORNER SW
COUNTY Douglas OREGON



ACCESSORIES ADDED THIS DATE: Oct. 10, 1963
MAGNETIC DECLINATION 20°

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
2 only						
40" Red Cedar	N 82 W	36.7	X	X	X	---
36" Fir stump	N 1 W	56.2	---	X	X	---

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: Salal, Ocean Spray, and Chinquapin
(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)
SLOPE FACES (GIVE BEARING IN DEGREES) S 65 W ON MINUS (-) 25 %

NORTH: + 40%

SOUTH: - 12%

EAST: + 37%

WEST: - 15%

GLO SURVEY RECORD
DATE: 1897
CORNER Stone
PRESENT CONDITION - (DESCRIBE FULLY - USE PAGE 2 IF NEEDED FOR EXPLANATION.)
Mound of stone

ACCESSORIES:

	BEARING-	LINKS-	FEET-	
12" Chinquapin	N 8 E	49	32.3	20"x4' rotted Chinquapin stub - A scribed slab from this tree is lying near the corner
12" Fir	S 58 E	73	48.2	24"x25' Fir snag - scribing visible
8" Fir	S 28 W	73	48.2	24" Fir - Face not opened
40" Cedar	N 83 W	59	38.9	40" Red cedar - face open - Scribing not visible

SURVEY RECORD
DATE:
PRESENT CONDITION:
Found in Field:
1957 U. S. Cadastral brass cap and 3 scribed Bts and USBT plates:
12" White fir - Plate: "47 lks. -S 47 W"
14"x20' Cedar snag - Plate: " 75 lks- N 48 1/2 W"
8" White Fir - Plate "17.8' N 11 W"

CORNER SET: Brass Cap MAG. DECL.: 20°

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:

BEARING-	FEET-	SURVEY -	
N 8 E	31.1	1897	Distance measured to center of tree
S 58 E	47.5	"	" " " face
S 28 W	48.2	"	" " " center of tree
N 83 W	38.0	"	" " " face
N 45 E	31.0	1957	" " " center of tree
S 48 E	48.8	"	" " " face
S 11 E	17.5	"	" " " "

WORK DONE FOR W. CO. FIELD NOTES IN BOOK:

BY: *Allen M. Casney* DATE: Oct. 9, 1963
LAND AGENT

UNDER THE SUPERVISION OF:

ASSISTED BY:
COPIES SENT TO:

CS 53/108-14