


PUBLIC LAND CORNERS

SPRINGFIELD
 SURVEY FILE

WEYERHAEUSER COMPANY
 SPRINGFIELD BRANCH

TOWNSHIP 24 S RANGE 3 W
 SECTION 1 CORNER N E
 COUNTY Douglas OREGON



ACCESSORIES ADDED THIS DATE:

MAGNETIC DECLINATION 20° E

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
64" Fir	East	42.6	—	X	X	—

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: O. G. Timber

(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)

SLOPE FACES (GIVE BEARING IN DEGREES) s 65 W ON MINUS (-) 18 %

NORTH: + 2% - 15' - Thence over ridge

SOUTH: -12% - 60'

EAST: + 15% - 50'

WEST: 17% - 60'

FROM CORNER -

WORK DONE FOR W. CO.

FIELD NOTES IN BOOK:

BY: M. D. Hale DATE: 5-6-63

~~ROCKWELL~~ - SURVEYOR

ASSISTED BY: H. E. Case

COPIES SENT TO:

UNDER THE SUPERVISION OF:

SEAL

PAGE 3

GLO SURVEY RECORD

DATE: 1894
 CORNER Post

PRESENT CONDITION - (DESCRIBE FULLY - USE PAGE 2 IF NEEDED FOR EXPLANATION.)

Gone

ACCESSORIES:

	BEARING-	LINKS-	FEET-	
60" Fir	S 70 E	56	37.0	Now blown down
18" Yew	S 24 W	59	39.0	OK
60" Fir	N 37 W	32	21.1	

W. Co. SURVEY RECORD DATE: 1954
 Set: 1/2" G.I.P.

PRESENT CONDITION:

20" Yew B.T. s 24 W 39.0' OK
60" Fir B.T. N 29 W 8.7 OK

CORNER SET: None MAG. DECL.: 20° E

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:

BEARING-	FEET-	SURVEY-	
S 24 W	39.0	W.Co.	20" Yew B.T.
N 30 W	8.6	W.Co.	62" Fir B.T.

CS53/111-1