

SPRINGFIELD
 SURVEY FILE


PUBLIC LAND CORNERS

WEYERHAEUSER COMPANY
 SPRINGFIELD BRANCH

TOWNSHIP 24 S RANGE 3 W

SECTION 6 CORNER NW

COUNTY Douglas OREGON



GLO SURVEY RECORD	PRESENT CONDITION - (DESCRIBE FULLY - USE PAGE 2 IF NEEDED FOR EXPLANATION.)									
DATE: <u>1950</u>										
CORNER <u>Iron post 3" by 3" with brass cap</u>	<u>Iron post & brass cap visible</u>									
ACCESSORIES:										
<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>BEARING-</th> <th>LINKS-</th> <th>FEET-</th> </tr> </thead> <tbody> <tr> <td><u>9" Fir</u></td> <td><u>s 48 E</u></td> <td><u>65</u></td> </tr> <tr> <td><u>7" Cedar</u></td> <td><u>S 43 1/2 W</u></td> <td><u>82</u></td> </tr> </tbody> </table>	BEARING-	LINKS-	FEET-	<u>9" Fir</u>	<u>s 48 E</u>	<u>65</u>	<u>7" Cedar</u>	<u>S 43 1/2 W</u>	<u>82</u>	<u>Fir is still standing but now a snag</u> <u>Scribbing is still visible</u> <u>Cedar has been knocked down by logging</u> <u>is now a 10" snag 6' in height.</u> <u>Scribbing is still legible but is part-</u> <u>ially torn from stump.</u>
BEARING-	LINKS-	FEET-								
<u>9" Fir</u>	<u>s 48 E</u>	<u>65</u>								
<u>7" Cedar</u>	<u>S 43 1/2 W</u>	<u>82</u>								
SURVEY RECORD	PRESENT CONDITION:									
DATE:										

CORNER SET: _____ MAG. DECL.: _____

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:			
BEARING-	FEET-	SURVEY -	
<u>S 48 E</u>	<u>43</u>	<u>G.L.O.</u>	<u>(Resurvey) B.T.</u>
<u>S 43 1/2 W</u>	<u>54</u>	<u>G.L.O.</u>	<u>(Resurvey) B. T.</u>

ACCESSORIES ADDED THIS DATE:

MAGNETIC DECLINATION _____

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
<u>19" Fir</u>	<u>N 7 E</u>	<u>20.6</u>	<u>---</u>	<u>X</u>	<u>X</u>	<u>---</u>
<u>8" Fir</u>	<u>N 62 E</u>	<u>35.8</u>	<u>---</u>	<u>X</u>	<u>X</u>	<u>---</u>
<u>12" Fir</u>	<u>S 59 E</u>	<u>34.6</u>	<u>---</u>	<u>X</u>	<u>X</u>	<u>---</u>
<u>12" Cedar</u>	<u>S 53 W</u>	<u>42.3</u>	<u>---</u>	<u>X</u>	<u>X</u>	<u>---</u>

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: Grasses, bracken fern, salal, & fir reproduction

(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)

SLOPE FACES (GIVE BEARING IN DEGREES) N 80 E ON MINUS (-) -30 %

NORTH: -29% for 40' to small stream, thence up about 40'

SOUTH: - 3% for 100' area a steeper

EAST: -30% for 50' break steeper

WEST: 15% for 200'

WORK DONE FOR W. CO.

FIELD NOTES IN BOOK:

By: Bruce Malcom DATE: Jan. 17, 1962

ENGINEER - SURVEYOR
 Ass't. Forester

ASSISTED BY: Bob Duncan

UNDER THE SUPERVISION OF:

COPIES SENT TO:

CS 53/11-13

48