


PUBLIC LAND CORNERS

SPRINGFIELD
SURVEY FILE

WEYERHAEUSER TIMBER COMPANY
SPRINGFIELD BRANCH

TOWNSHIP 24 S RANGE 3 W
SECTION 11 CORNER NW
COUNTY Douglas OREGON



GLO SURVEY RECORD

DATE: 1871
CORNER Post

PRESENT CONDITION - (DESCRIBE FULLY - USE PAGE 2 IF NEEDED FOR EXPLANATION.)

Post gone. Found an old "X" on a fir tree N 13° W 14' which corresponds with the X's on trees near corners in this general area which dates back to about 1905.

ACCESSORIES:

	BEARING-	LINKS-	FEET-
8" Maple	N 85° E	22	14.5
6" Maple	S 20° E	25	16.5
8" Maple	S 32° W	11	7.2
8" Maple	N 5° W	29	19.1

SURVEY RECORD

PRESENT CONDITION: _____

CORNER SET: Sec 2" x 2" x 4" Hem. Post MAG. DECL.: 20°

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:

BEARING-	FEET-	SURVEY -	
S 32° W	7.2	G.L.O	Clump of Maples - old ax marks
N 5° W	19.1	G.L.O.	Remains of old maple.

ACCESSORIES ADDED THIS DATE:

MAGNETIC DECLINATION 20° E

	BEARING	FEET	ORIG.B.T.	"W" NAIL	PLATE	BRASS DISC
54" Fir	N 68° E	13.9	--	X	X	--
60" Fir	N 13° W	14.1	--	X	X	--
27" Fir	S 17° E	38.6	--	X	X	--
48" Fir	S 17° W	49.7	--	X	X	--

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: Old Growth Fir, Hem, V-Maple, Salal & Fern

(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)

SLOPE FACES (GIVE BEARING IN DEGREES) S 32° E ON MINUS (-) 28 %
ABOUT 40'

NORTH: + 22%

SOUTH: - 22%

EAST: - 24% for 30' to E small creek; course S 12° W

WEST: - 7% for 100' (955' West to ridge and Coon Creek Divide)

WORK DONE FOR W. T. CO.:

FIELD NOTES IN BOOK: _____

BY: M. D. Hale DATE: 6-16-59

UNDER THE SUPERVISION OF:

~~_____~~ - SURVEYOR

ASSISTED BY: W. W. Dimon

COPIES SENT TO: _____

SEAL PAGE 3

FILED
RECEIVED

JUN 28 1961

CS 53/111-16