


SPRINGFIELD
 SURVEY FILE

PUBLIC LAND CORNERS

WEYERHAEUSER TIMBER COMPANY
 SPRINGFIELD BRANCH



TOWNSHIP 25 S RANGE 2 W
 SECTION 8 CORNER 1/16 "K"
 COUNTY Douglas OREGON

GLO SURVEY RECORD			
CORNER		DATE:	
ACCESSORIES:			
BEARING-	LINKS-	FEET-	

PRESENT CONDITION - (DESCRIBE FULLY -
 USE PAGE 2 IF NEEDED FOR EXPLANATION.)

Hosford SURVEY RECORD			
DATE:		1958	
1 1/2" X 36" Iron Pipe			
30" Hemlock	N 52 E	30.2'	30" Hemlock Scribed
30" Cedar	N 73 W	30.6'	30" Cedar Scribed

PRESENT CONDITION: 7-29-59
 Found

CORNER SET: 1 1/2" X 36" Iron pipe set by Hosford MAG. DECL.: 20°

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:			
BEARING-	FEET-	SURVEY -	
N 52 E	30.2	Hosford	30" Hemlock
N 73 W	30.6	Hosford	30" Cedar

ACCESSORIES ADDED THIS DATE:

MAGNETIC DECLINATION 20°

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
30" Cedar	N 73 W	30.2	Hosford	X	X	-----
58" Fir	S 10 E	22.6	-----	X	X	-----

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: Salal, Fern.

(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)

SLOPE FACES (GIVE BEARING IN DEGREES) N 35 E ON MINUS (-) 50 %

FROM CORNER 1

NORTH: - 46% 50' to draw C-NE

SOUTH: + 36% Old growth to East - to West to be logged 1959

EAST: - 28% 40' to draw - C-N

WEST: + 24%

WORK DONE FOR W. T. CO.:

FIELD NOTES IN BOOK:

BY: Allen McChesney DATE: July 29, 1959
 ENGINEER SURVEYOR

UNDER THE SUPERVISION OF:

ASSISTED BY:

COPIES SENT TO:

SEAL

67

CS 53/112-7