

SPRINGFIELD
SURVEY FILE


PUBLIC LAND CORNERS

WEYERHAEUSER TIMBER COMPANY
SPRINGFIELD BRANCH

TOWNSHIP 25 S RANGE 2 W

SECTION 10 CORNER S 1/4

COUNTY Douglas OREGON



ACCESSORIES ADDED THIS DATE:

MAGNETIC DECLINATION 20°

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
66" fir	N 66 E	19.8	CS	X	X	-
8" fir	S 39 E	38.1	CS	X	X	-

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: Salal

(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)

SLOPE FACES (GIVE BEARING IN DEGREES) South ON MINUS (-) 60 %

NORTH: +45% uncut pole and scattered old growth fir

SOUTH: -60% uncut pole and scattered old growth fir
640' to plate on 3" alder on South side rock cr. road.

EAST: 0% uncut pole and scattered old growth.

WEST: 0% uncut pole and scattered old growth.

FROM CORNER -

GLO SURVEY RECORD				PRESENT CONDITION - (DESCRIBE FULLY - USE PAGE 2 IF NEEDED FOR EXPLANATION.)
DATE: <u>1900</u>				
CORNER <u>Stone 14'x10'x6"</u>				<u>Found in mound of rocks</u>
ACCESSORIES:				
BEARING-	LINKS-	FEET-		
6" chinquapin	S 12 E	38	25.1	8" dead chinquapin - faces visible but scribing rotted away.
6" chinquapin	N 17 W	32	21.1	8"x8' chinquapin stub. scribing visible.
SURVEY RECORD				PRESENT CONDITION: <u>February 11, 1960</u>
DATE: <u>1948</u>				
County <u>Douglas</u>				
Found stone and original Bt's				
Marked:				
66" fir N58E 20.0'				66" fir - bark scribing visible.
6" fir S46E 37.6				10" fir - face scars visible.

CORNER SET: Stone as found. Drove laurel MAG. DECL.: 20°

post beside stone.

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:

BEARING-	FEET-	SURVEY -	
S9E	24.6	GLO	Distances to face
N17W	20.7	GLO	Distances to face
N68E	20.0	CS	Distances to face
S 39 E	38.1	CS	Distances to face

PAGE 1

WORK DONE FOR W. T. CO.:

FIELD NOTES IN BOOK:

BY: Allen M. Cherry DATE: February 11, 1960
-ENGINEER-SURVEYOR-

UNDER THE SUPERVISION OF:

ASSISTED BY: William Wilt

COPIES SENT TO:

SEAL PAGE 3

CS 53/112-13