13

SPRINGFIELD SURVEY FILE

PUBLIC LAND CORNERS

WEYERHAEUSER COMPANY
SPRINGFIELD BRANCH

TOWNSHIP 25 S RANGE 3 W

SECTION 34 CORNER "G" (M1/16)

COUNTY ~~Douglas~~ OREGON



GLO SURVEY RECORD

DATE:

CORNER (No GLO Record)

ACCESSORIES:

	BEARING-	LINKS-	FEET-

PRESENT CONDITION - (DESCRIBE FULLY - USE PAGE 2 IF NEEDED FOR EXPLANATION.)

SURVEY RECORD

DATE:

PRESENT CONDITION:

CORNER SET: 1"x48" Iron Pipe set MAG. DECL.: 20°

(Set at point established by William G. Barnes Survey 6/63)

BEARING AND DISTANCE TO ABOVE IDENTIFIED SURVEY ACCESSORIES:

BEARING-	FEET-	SURVEY-	

PAGE 1

ACCESSORIES ADDED THIS DATE:

MAGNETIC DECLINATION 20°

	BEARING	FEET	ORIG. B.T.	"W" NAIL	PLATE	BRASS DISC
10" Red Cedar	N 36° E	19.0	----	X	X	No. 2128
8" Douglas Fir	N 29° W	17.0	----	X	X	2128

IDENTIFIED ON PHOTO:

INFORMATION ON LOCATION OF CORNER AS NOW SET:

GROUND COVER: 40 Yr. Old 2nd Gr. Fir; scattered O.G. Fir and Sugar Pine

(USING FORM LINES SKETCH TOPOG AT CORNER ON PAGE 2 PLAT)

SLOPE FACES (GIVE BEARING IN DEGREES) South ON MINUS (-) [illegible] %

FROM CORNER -

NORTH: + 30%; West - O.G. Fir; East - logged about 5 yrs. with scattered 40 Yr. Old Fir and Hemlock.

SOUTH: -22%; West - uncut O.G. Fir to be logged 1963; East - logged about 5 Yrs. with

EAST: -5%; logged as above noted.

WEST: +14%; Uncut O.G. & Sugar Pine; to South to be logged 1963.

WORK DONE FOR W. CO.

FIELD NOTES IN BOOK:

BY: William L. Tilt DATE: 6/27/63

~~ENGINEER - SURVEYOR~~
LAND AGENT

ASSISTED BY:

COPIES SENT TO:

UNDER THE SUPERVISION OF:

SEAL

PAGE 3

CS53/113-13