

526 | 525
535 | 536

Renew Sec. CoR, T265R3W

Fd. following BT's at COR, -

ORIG. 20" Now 25" S. 35° W. 13 3/4 ft. alive
previously opened & shows "S" scribe.

ORIG. 20" Now 36" FIR (STAMP) N. 30° W. 21 1/2 ft.
find "S" & fragmentary BRASS scribe.

also find 3/4" I.P. & aluminum cap 25

Recorded in Ren. # 102 which Bears
S. 10° W. 4 3/4 ft. FROM ^{TRUE} ~~2nd~~ COR.

Location, we set 1" I.P. & BRASS CAP

Mkd. "COUNTY SURVEYORS OFFICE 1966

T265R3W ^{526 | 525} 535 | 536 we use BT's

previously Mkd by SHRUM - New Bearings

& Distances from BRASS CAP 25 follows -

10" Maple S. 70 1/2° E. 46 3/4 ft.

Mkd. " S 36 BT " & Aluminum Tag "RE 4287"

8" Yew N. 57° E. 27 1/2 ft.

Mkd. " S 25 BT " & Alum. Tag "RE 4287"

18" Cedar N. 85° W. 30° ft.

Mkd. " S 26 BT " & Alum. Tag "RE 4287"

we use ORIG. BT TO S.W.

Jan 28, 1966

J.W.B.
V.R.P.
M.S.
D.L.

+ X R. Tracy

*141

S. S. File No. 54/7-17