

Renew S. $\frac{1}{4}$ COR S. 8 T255 R7W
 Fd. Rock Bluff with faint MKs. CS B0 as
 called for in Ren. #15 by J.W. Cole
 which Bears S. 31° E. 64[±] ft.
 4[±] ft. above ground - ~~Fd. P.B.T.~~
 that was apparently used by Cole
 48" FIR S. 45° W. 33[±] ft. (face)
 2 live-shows " $\frac{1}{4}$ BT" BARK scribe
 we Rescribe " $\frac{1}{4}$ S CS BT" (Low and along
 side old scribe) - Record Bearing, N. 59° W.
 48" FIR SNag bears N. 65° E. 19[±] ft.
 (Record N. 36° E) NOT 33'
 Badly Burned & Decayed on SW side - we
 believe this to be other orig. BT.
 at COR. point set 1" I.P. & BRASS CAP
 MKd. "COUNTY SURVEYORS OFFICE
 1970 T255 $\frac{1}{4}$ S 8 R7W" & MK.
 New B.T. -
 8" chinquapin S. 74° E. 27[±] ft.
 MKd. " $\frac{1}{4}$ S 8 CS BT"
 This COR. Lies on very steep
 Rocky Northernly slope. Note -
 Brass cap Reset 10[±] ft. N. 31° W. on 7-27-70
 To use Cole's Record Dist. of 64[±] ft. from Bluff,
 May 13, 1970 & July 27, 1970 U.R.T. W.D.P.
 F.W.B.

#98 R.T. Ray

C. S. File No. 54/10-19
 D. X. B.
 S. W. B.