

Renew Sec. Cor, R9W | ⁵³⁰/₃₃₁ T23S R8W,

Fd. sand stone 16" x 6" x 8" firmly set but covered 6" deep with loose dirt & mkd. with 1 notch on S. & 5 notches on N. Edges & find B.T.s as follows -

Orig. 5" Now 18" FIR N. 41° E, 3³ ft.

alive - shows good SCAR - we Rescribe

" T23S R8W S30 CS BT "

Orig. 10" Now 30" FIR S. 61° E, 13² ft.

alive shows fair SCAR - we Rescribe

" T23S R8W S31 CS BT "

Orig. 14" Now 38" FIR S. 54° W, 75² ft.

alive - shows good SCAR - do not open.

Set 1" I.P. & BRASS COP. MKD. "COUNTY

SURVEYOR'S OFFICE 1967

T23S R9W | ⁵³⁰/₃₁₁ R8W " & Reset

stone along side. This cor. lies on E. edge of small creek course S. 10° E.

FILED

Jan. 11, 1967

RECEIVED V.R.T.

J.H.

JAN 11 1967

J.R. Tracy

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

54
21-592

J.W.B.

C.S. File No. 54/12-8