

515 | 514

Renew Sec. COR. 522 | 523 T265 R7W

Fd. 3/4" I.P. with Elbow on top for COR.  
& STump of BTs as Recorded in Ren #2  
as follows -

30" Now 41" Fir N. 18° W. 27° ft. (face)  
STump - No scribe fd.

36" Now 48" Fir S. 63 1/2° W. 46 1/2 ft. (face)  
STump - "BT" BARK scribe.

30" Now 42" Fir S. 42 1/2° E. 22 1/2 ft. (face)  
STump - BARK faced off - Badly flaked - No scribe.  
12" Now 24" Fir East 41 1/2 ft. (face)

Recorded as 31 1/2 ft. we open & find "BT" scribe.  
Set 1" I.P. & BRASS Cap at COR. MKd.

"COUNTY SURVEYORS OFFICE 1966 T265

515 | 514  
522 | 523

R7W" & MK New BTs -

5" W. Fir N. 64° E. 12 1/2 ft.

Mkd. "S 14 CS BT"

14" B. Oak N. 31° W. 23 1/2 ft.

Mkd. "T265 R7W S 15 CS BT"

6" W. Fir S. 20° W. 23 1/2 ft.

Mkd. "S 22 CS BT"

5" D. Fir S. 23° E. 24 1/2 ft.

Mkd. "S 23 CS BT"

E.-W. fence Bears 8° ft. South.

9 March 22, 1966

~~X<sup>763</sup> [Signature]~~

U.R.T.

M.S.

J.S. 54/23-8

SEE OVER

N.F.S' T26S R7W

$\frac{1}{4}$   $\frac{514}{523}$

$\frac{1}{4}$  515 | 514 #11

Fd. Cor. T26S R7W Post

East  $\frac{1}{16}$  of  $\frac{514}{523}$  25 set by Stewart in 1922.

Fd. Stump of BT

18" Fir S, 23° E. 23 ± ft

"BT" Bark scribe. & 2 1/2"

axle with a 6" flange on top for cor.

March 22, 1966

U.P.T.  
M.S.  
J.H.

~~FILED~~  
FILED  
RECEIVED

MAR 25 1966

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

8A

DIETZGEN NO. 385-6