

516 | 515

Renew Sec. Cor. 521 | 522 T255 R3W

Fd. GLO. BRASS Cap MKd. T255 R3W

516 | 515
521 | 522 1943" with steel fence post

Set alongside 1943 B.T. as follows -

16" FIR S. 12° E. 13 3/4 ft Now S N 29

show" T255 R3W S BT" scribe on unhealed Blaze.

18" FIR S. 6 1/4° W. 25 1/2 ft.

Now S N 29 shows scribe on unhealed Blaze.

20" FIR N. 32 1/2° W. 4° ft.

Now shattered S N 29 - scribed half lying

face down - fragmentary Reverse

scribe visible. other B.T.s gone we

MARK New B.T.s -

12" Red Cedar N. 5° W. 30 5/8 ft.

Mkd. " T255 R3W 516 CS BT "

16" Hemlock N. 38° E. 38° ft.

Mkd. " T255 R3W 515 CS BT "

9" Hemlock S. 64° W. 29 5/8 ft.

Mkd. " T255 R3W 521 CS BT "

4" Hemlock S. 61° E. 15 1/2 ft.

Mkd. " S 22 CS BT "

FILED

RECEIVED

V.R.T.

Sept. 16, 1966

SEP 16 1966

[Signature]

COUNTY SURVEYOR

1928

O.W. J. W.B.
C.S. File No. 64/27

DOUGLAS COUNTY, ORE.