

Renew  $\frac{1}{4}$  530/529 T265 R2W

Fd. ORIG. COR. Stone 7" X 8" X 10" firmly  
set & faint " $\frac{1}{4}$ " on W. & O.B.T.s as follows  
ORIG. 12" Now 20" cedar S. 58° E. 3 $\frac{3}{4}$  ft. (face)

2 live - shows good SCAR - do not open.

ORIG. 10" Now 21" cedar N. 82° W. 17 $\frac{3}{4}$  ft. (face)

2 live - previously opened & shows -

" $\frac{1}{4}$  530 BT" scribe & we find chips with  
Reverse scribe on ground. - set 1" I.P.

& BRASS CAP MKD. "COUNTY SURVEYORS  
OFFICE 1967 T265  $\frac{1}{4}$  530/529 R2W"  
& MK. new B.T.s -

10" Hemlock N. 70° W. 21 $\frac{1}{2}$  ft.  
MKD. " $\frac{1}{4}$  530 CS BT"

7" Hemlock N. 55° E. 21 $\frac{1}{2}$  ft.  
MKD. " $\frac{1}{4}$  529 CS BT"

This cor. lies on moderate SE.  
Slope approx. 400 ft. N. of  
Power line from River to Top  
of Mtn. along Bob Creek.

Reset cor. stone along side.

July 18, 1967

V.R.T.  
J.H.  
P.W.

*V.R.T. [Signature]*

#47

a.n. J.W.B

C.S. File No. 54/90-19