

FD. 1" I. PIPE AT 1/4 COR.
SEC. 24, & ALL BTR. R.C.#64

SOUTH 114.07'

FD. BRASS CAP AT 1/4 COR.
SEC. 19, & ALL BTR. R.C.#197

SET BRASS CAP, WITH STEEL
FENCE POST ALONG SIDE, SET
BY PROPORTION FOR SEC. COR.
TO SEC. 24 & 25. D.C. MKD. COUNTY
SURVEYOR'S OFFICE 1969, T.30S.,
R. 6 W. S. 24, S. 25. BEARING
OBJECTS: SET 2, 3/4" I. RODS
WEST 18.0' + 20.0'; STEEL
FENCE POST, SOUTH 53.30'

SET BRASS CAP BY
PROPORTION FOR THE COR.
SECS. 19 & 30, WITH STEEL
FENCE POST ALONG SIDE,
D.C. MKD. COUNTY SURVEYOR'S
OFFICE, 1969, T.30S., R. 5 W., S. 19
S. 30. BEARING OBJECTS:
SET 2, 3/4" I. RODS, EAST 18.0' + 20.0'
SET STEEL FENCE POST NORTH 53.30'

NOTE: BEARINGS ARE
MAGNETIC, WITH A VAR.
OF 20°00'

DO NOT REMOVE FROM OFFICE

T. 30 S., R. 6 W.

T. 30 S., R. 5 W.

SET BRASS CAP FOR 1/4 COR.
SEC. 25 BY PROPORTION,
MKD. COUNTY SURVEYOR'S
OFFICE 1969, T.30S., R. 6 W. SET
NEW BTR. 12" OAK S. 26° W
127.4'; MKD. 1/4 S. 25 C.S. BT.
10" M. OAK S. 02° W. SEE 60'; MKD.
1/4 S. 25 C.S. BT. NOTE: SET 5'
STEEL FENCE POST ALONG
SIDE BRASS CAP.

NOTE: FD. 20" N. OAK, S. 0° 12' W. 214.75'
FROM 1/4 COR. SEC. 25, MKD. 1/4 S. ON S. E.
FACE. THIS TREE NOT USED. SEE C.S. #10-
78 & R.D. 55, PAGE M.

SET BRASS CAP FOR 1/4 COR.
SEC. 30 BY PROPORTION, MKD.
COUNTY SURVEYOR'S OFFICE
1969, T.30S., R. 5 W., S. 30. NEW BTR:
26" M. OAK, S. 43° E 71.0' MKD. 1/4 S. 30
C.S. BT., 3" LAUREL, S. 16° E 53.2';
MKD. 1/4 S. 30 C.S. BT. NOTE: SET 4'
STEEL FENCE POST ALONG SIDE
BRASS CAP.

COUNTY SURVEYOR'S OFFICE
DOUGLAS COUNTY OREGON
SURVEY TO SET SECTION COR.
BETWEEN T.30S. R. 5 AND 6 W. W.M.

JAMES W. BYRON COUNTY SURVEYOR
SURVEYED DEC. 24, 1968 SCALE 1" = 600'
SURVEYED FOR DOUGLAS CO.

**COUNTY SURVEYORS FILE DATA
DO NOT REMOVE FROM OFFICE**

FD. 1" I. PIPE AT SEC. COR.
25 & 30, & 1 BT. R.C.#54, NEW
BT: 14" D. P.M. S. 49° W. 27.5'
MKD. T.30S., R. 6 W. 536 C.S.
BT.

S. 0° 59' E. 92.19'
FD. 1" I. PIPE AT SEC. COR. SEC. 30
& 31, & ALL BTR. R.C.#223.

REGISTERED
OREGON
LAND SURVEYOR

James W. Byron

JAMES W. BYRON
303