Renew Wit. Cor. to Cor. #20 of HES 143 T29S R1E
Fd. Cor. Stone in place & Mkd. "WC
20 HES 143" & old BT. —
Orig. 6"Nov 18" Fir N. 67½° W. 33 ± ft.
Now Stump - we open & find scribed
Reverse - other O.B.T. gone - in place of
old Cor. Stone Set 1" I.P. & Brass Cap
for Witness Cor. Mkd. "COUNTY
SURVEYORS OFFICE 1969 T29S
WIT. COR. → COR. #20 H.E.S. 143
R1E" Note Trye Cor. Bears S. 70° 07' E.
39 ± ft. in Creek. - Mk. New B.T.s -
8" W. Fir. N. 34° W. 31 ± ft.
Mkd. "WC 20 HES 143 CS BT"
10" W. Fir N. 74° W. 27 ± ft.
Mkd. "WC 20 HES 143 CS BT"
This Cor. Lies on Flat in Dense
Vine Maple Brush - Note - See over.

Dec. 16, 1969

V.R.T.
J.G.H.

V R Tracy

O.K.
S.D.M.

122'

C. S. File No. 54182-99

The Record Dist. in field
Notes Between Cor's # 20 & 21
is 8.96 chains- On Geo.
Plat, The same Line shows
To be 6.98 chains- in Doing
I found The 6.98 chs. dist.
To be more correct. Also
The Remains of The Orig.
Listing Cor. would be on out
This same Location - a blazed
Stump bears S. 81½° E. 15 Lks.
We open'd find obliterated Blaze
Also Remains of Scribe on a Stump
To S.E. facing Cor. Stump Above
Also obliterated.

O.K.
F.W.M.

DIETZGEN NO. 385-6