CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

As surveyed by Charles L. Campbell, Deputy Surveyor, under contract No. 747, dated 1902.

Original survey states: Marked a fir, 14 ins. diam., for ¼ sec. cor., marked ¼ S 13 on W. and S 18 on E. faces, from which

A fir, 18 ins. diam., bears S 54* E., 20 lks dist. Marked ¼ S B T

A fir, 24 ins. diam., bears S 20½* W., 30 lks. dist. Marked ¼ S B T

DIAGRAM

T32S R2W WM

S18

Description of corner evidence found:

A fir, 38" diam., Iopened face and fount ¼ S 18 B T in good condition

Description of monument and accessories I established to perpetuate the original location of this corner

Using record bearing and distance I set a 2" by 30" galvanized iron pipe, with brass cap, 24" in the ground.

I stamped the disk

¼
S18
1968
OLS536

From the pipe monument, the original bearing tree is:

A fir, 38 ins. diam., bears S 20* W 19.8'
Marked ¼ S 18 B T

I marked a fir, 40 ins. diam., bears S 27* E, 34.2'
Marked ¼ S 18 B T

I placed bearing tree tags on all bearing trees and facing the monument.

REGISTERED
OREGON
LAND SURVEYOR

Glenn S. Baughman

JULY 14, 1961
GLENN S. BAUGHMAN
536

Office of Surveyor County of Douglas
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 23 day of August, 19 68, at 10 o'clock A m., (signed)

James C. Byram (COUNTY OFFICIAL) by (DEPUTY)

FILED
RECEIVED

AUG 23 1968

COUNTY SURVEYOR
DOUGLAS COUNTY, ORE.

#25 Form R6-7100-57 (9/66)

700432 / 100446

C. S. File No. 55/87 -3