CERTIFIED RECORD OF LAND CORNER MONUMENTATION

History of original corner establishment:

As surveyed by William Thiele

Under Contract # 567 Dated 1891

He states that he erected a mound of stone 1 1/2 ft high, 2 ft base alongside a sandstone 9x8x7 ins, 6 ins. in the ground, marked 1/4 on N face for 1/4 sec cor.

DIAGRAM

T20S R11W
1/4 cor S29/S32

Description of corner evidence found:

None

Description of monument and accessories I established to perpetuate the original location of this corner

I set a 2" x 30" galvanized iron pipe with a brass cap, 24" in the ground

I stamped the disk .....

From the pipe monument I marked new bearing trees,
a 23" hemlock bears S3°W at 22.4 ft.
a 21" hemlock bears N25°30' E at 44,3 ft.

1/4 Cor
T20S R11W
1/4 S29/S32
L.S. 536
1970

REGISTERED
OREGON
LAND SURVEYOR

Glenn S. Baughman

JULY 14, 1960
GLENN S. BAUGHMAN
536

Office of SURVEYOR County of DOUGLAS
State of Oregon, I hereby certify that the within instrument was filed in this office for record on the 28 day of APRIL, 1970, at 11 o'clock A.m., (signed)
James W. Byrom (COUNTY OFFICIAL) by ..... (DEPUTY)

✓ #97

Form R6-7100-57 (9/66)

C.S File 55 1147-1

Map File M39 + 48