

FILED  
RECEIVED

JAN 19 1972

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

SURVEY TO RE-ESTABLISH  
SW COR SEC 19 T21S R9W  
MADE FOR BUREAU OF LAND MANAGEMENT  
BY COOS HEAD TIMBER CO.

Marked:  
● 30" Fir brs N.45°00'W for 84' ft.  
to ♁ tree Tree faced and  
scribed "Sec Cor"

Marked:  
● 36" Fir brs N 9°00'E for 62' ft.  
to ♁ tree Tree faced and  
scribed "Sec. 19 Cor"

© Orig B.T. - 1894 Survey by Alonzo Gesner  
Re-establish Sec. Cor. from this B.T.  
Find: 34" Fir brs N.49°45'W for 72 lks.  
to face of tree.

REGISTERED  
PROFESSIONAL  
LAND SURVEYOR

△ Set:  
1/2" X 18" reinforcing rod 8" into  
solid sandstone on W. facing slope

OREGON  
JULY 11, 1969  
C. WYLIE SMITH III  
910

LEGEND

- ◎ Bearing Tree Found
- Bearing Tree Set
- △ Corner Set

Basis of Bearing: B.L.M. Survey 1966

Initial Point of Survey: Blazed Lines

Dec. 30, 1971

Decl. 20°00'



FILED   
RECEIVED

JAN 19 1972

COUNTY SURVEYOR  
DOUGLAS COUNTY, ORE.

SURVEY TO RE-ESTABLISH SOUTHWEST CORNER  
SECTION 19, TOWNSHIP 21 SOUTH, RANGE 9 WEST, W.M.

MADE FOR BUREAU OF LAND MANAGEMENT  
BY  
COOS HEAD TIMBER COMPANY

In December of 1970 while slope staking for Road No. 21-9-19.1, BLM Contract No. 71-10, this corner was observed. The blazed lines to the East, North and South were freshened and repainted at that time.

Upon returning to this corner in December 1971, I find that a slide from the newly constructed road has obliterated the corner and all evidence set in the re-survey of the East boundary of Township 21 South, Range 10 West in December 1919. However, I do find axe marks and a grown-over face on a Douglas fir that fits the description of a bearing tree set by Alonzo Gesner August 30, 1894.


My basis of bearing is a survey of the S-line of Section 19 by Calvert Sartz of the Bureau of Land Management made February 1966. Corrected Decl. from this survey is  $20^{\circ}$  E. which I set on my compass. I then jig into the approximate position of the original corner by sighting along blazed lines to the N.-S. and E. I then checked the location of this point against the bearing tree referred to in Gesner's survey of 1894. The point agrees with Gesner's bearing tree. From the bearing tree I set a 1/2" x 18" reinforcing rod at this point. I faced and scribed two additional bearing trees to witness this point.

SURVEYED BY R. F. GREENE  
Forest Engineer  
December 30, 1971

CHAIN MAN Dan Woods

#17 - T21-9  
#38 - T21-10

This survey was done under my supervision.

  
C. Wylie Smith III

January 14, 1972.

C. S. File No. 55/230 b